


Micro-Ray

MICRO-RAY ELECTRONICS, INC.




www.micro-ray.com

REVISION RECORD

REV.	DESCRIPTION	ECN No.	APPROVED	DATE



P.C.B. LAYOUT



UL/CUL Technical Data		c [®]  us		
Use Group		B	C	D
Rated Voltage	[V]	300	-	300
Rated Current	[A]	8	-	8
Wire Range Solid/Stranded	[AWG]	-		
Withstanding Voltage		1600V/1Min		
IEC Technical Data		IEC61984		
Overvoltage Category		III	III	II
Contamination Class		3	2	2
Rated Voltage	[V]	160	160	320
Rated Current	[A]	7	7	7
Impulse withstand voltage	[KV]	2.5	2.5	2.5
Conductor cross section Solid/ flexible		-		
		[mm²]		
Material				
Insulation Material		PA66		
Inflammability		UL94V-0		
Contact Material		Copper alloy		
Contactive Coating		Sn Plated		
Other Data				
Pitch	Poles	[mm] / [P]		
Stripping Length		[mm]		
Screw	Torque(Max)	[N.m]		
Operating temperature		[°C]		
Soldering temperature		260°C/5S		
Pin Dimensions		[mm]		
PCB	PCB Hole Diameter	[mm]		

linear dimension(Tolerances Standard GB/T 14486-2008)


— □ ⊥

variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 100	over 10 to 100	over 100 to 100
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30

Micro-Ray

MICRO-RAY ELECTRONICS, INC.

THIRD ANGLE PROJECTION



/ V0
REV

TITLE

MR-15EDGA-3.81-XXP-1YY-00A