




Micro-Ray

MICRO-RAY ELECTRONICS, INC.

www.micro-ray.com

REVISION RECORD

REV.	DESCRIPTION	ECN No.	APPROVED	DATE



UL/CUL Technical Data		c  us		
Use Group		B	C	D
Rated Voltage [V]		300	-	300
Rated Current [A]		8	-	8
Wire Range Solid/Stranded [AWG]		28-16		
Withstanding Voltage		1600V/1Min		
IEC Technical Data				
Overvoltage Category		III	III	II
Contamination Class		3	2	2
Rated Voltage [V]		160	160	320
Rated Current [A]		8	8	8
Impulse withstand voltage [KV]		2.5	2.5	2.5
Conductor cross section Solid/ flexible [mm ²]		0.2-1.5		
Material				
Insulation Material		PA66		
Inflammability		UL94V-0		
Contact Material		Copper alloy		
Contactive Coating		Sn Plated		
Other Data				
Pitch	Poles [mm] / [P]	3.5 / 02-24		
Stripping Length [mm]		6-7		
Screw	Torque(Max) [N.m]	M2/0.2		
Operating temperature [°C]		-40~105		
Soldering temperature		-		
Pin Dimensions [mm]		-		
PCB Hole Diameter [mm]		-		

linear dimension(Tolerances Standard GB/T 14486-2008)


— ∠ ⊥

variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

Micro-Ray

MICRO-RAY ELECTRONICS, INC.

/THIRD ANGLE PROJECTION



/ V0
REV

TITLE

MR-15EDGKAM-3.5-XXP-1YY-00A