





Micro-Ray

MICRO-RAY ELECTRONICS, INC.

www.micro-ray.com

REVISION RECORD

REV.	DESCRIPTION	ECN No.	APPROVED	DATE



UL/CUL Technical Data

Use Group	B	C	D
Rated Voltage [V]	300	-	300
Rated Current [A]	8	-	8
Wire Range Solid/Stranded [AWG]	28-16		
Withstanding Voltage	1600V/1Min		

IEC Technical Data

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	160	160	320
Rated Current [A]	8	8	8
Impulse withstand voltage [KV]	2.5	2.5	2.5

Conductor cross section Solid/ flexible [mm ²]	0.2-1.5
--	---------

Material	
Insulation Material	PA66
Inflammability	UL94V-0
Contact Material	Copper alloy
Contactive Coating	Sn Plated

Other Data	
Pitch Poles [mm] / [P]	3.5 / 02-24
Stripping Length [mm]	7-8
Screw Torque(Max) [N.m]	-
Operating temperature [°C]	-40~105
Soldering temperature	-
Pin Dimensions [mm]	-
PCB PCB Hole Diameter [mm]	-

linear dimension(Tolerances Standard GB/T 14486-2008)




variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

Micro-Ray

MICRO-RAY ELECTRONICS, INC.

第三视角/THIRD ANGLE PROJECTION



版本 / REV V0

TITLE

MR-15EDGKDM-3.5-XXP-1YY-00A