




Micro-Ray

MICRO-RAY ELECTRONICS, INC.

www.micro-ray.com

REVISION RECORD

REV.	DESCRIPTION	ECN No.	APPROVED	DATE



UL/CUL Technical Data		cFUS		
Use Group		B	C	D
Rated Voltage	[V]	300	-	300
Rated Current	[A]	15	-	10
Wire Range Solid/Stranded	[AWG]	28-12		
Withstanding Voltage		1600V/1Min		
IEC Technical Data		IEC61984		
Overvoltage Category		III	III	II
Contamination Class		3	2	2
Rated Voltage	[V]	250	320	630
Rated Current	[A]	12	12	12
Impulse withstand voltage	[KV]	4.0	4.0	4.0
Conductor cross section Solid/ flexible	[mm²]	0.2-2.5		
Material				
Insulation Material		PA66		
Inflammability		UL94V-0		
Contact Material		Copper alloy		
Contactive Coating		Ni Plated		
Other Data				
Pitch	Poles [mm] / [P]	5.08 / 02-24		
Stripping Length	[mm]	7~8		
Screw	Torque(Max) [N.m]	M3/0.5		
Operating temperature	[°C]	-40~105		
Pin Dimensions	[mm]	-		
PCB Hole Diameter	[mm]	-		

linear dimension(Tolerances Standard GB/T 14486-2008)


— □ ⊥

variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 0.60
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30

Micro-Ray

MICRO-RAY ELECTRONICS, INC.

/THIRD ANGLE PROJECTION



/ V0
REV

TITLE

MR-2EDGKF-5.08-XXP-1YY-00A