

Models(Φ22)(Applicable to 25mm Mounting Hole)

Shape	Part Number	Color	Operating Voltage	Dimensions	Notes
Φ22 Flashing Light	MR-AD16-22S/△/▲	Single-color Flashing Light	AC/DC 12V AC/DC 24V AC 110V AC 220V AC 380V		Screw Terminal
	MR-AD16-22SS/△△/▲	Dual-color Flashing Light			Anti-electric Shock Structure
Φ22 Metal Frame Flashing Light	MR-AD16-22GQ-D/△/▲	Single-color Steady Light			Anti-interference Type can be customized
	MR-AD16-22GQ-S/△/▲	Single-color Flashing Light			Other illumination color can be customized
	MR-AD16-22GQ-SS/△△/▲	Dual-color Flashing Light			IP40/IP65(Optional)
Φ22 Buzzer	MR-AD16-22M/▲	Continuous Sound			Buzzer Volume: ≥80dB(10cm)
	MR-AD16-22S/△/▲	Single-color Flashing Light			
	MR-AD16-22SM/△/▲	Flashing Light ? Intermittent Sound			Continuous Sound Intermittent Sound le≤35mA
Φ22 Metal Frame Buzzer	MR-AD16-22GQ-M/▲	Continuous Sound			
	MR-AD16-22GQ-SM/△/▲	Flashing Light ? Intermittent Sound			
	MR-AD16-22GQ-SSM/△△/▲	Dual-color Flashing Light Intermittent Sound			

PART NUMBERS ON THIS DRAWING

MR-AD16-22GQ-D MR-AD16-22GQ-M MR-AD16-22GQ-S MR-AD16-22GQ-SM MR-AD16-22GQ-SS
MR-AD16-22GQ-SSM MR-AD16-22M MR-AD16-22S MR-AD16-22SM MR-AD16-22SS

Ø22 MM FLASHING LIGHT AND BUZZER

MR-AD16-22 SERIES

Micro-Ray

PART NO

MR-AD16-22

DWG NO

MR-AD16-22

SHEET

1 OF 1

REV

A

UNITS: mm

SCALE: NTS - DO NOT SCALE

SIZE

A4

DATE

2026-09-22