


Nickel Plated Brass
MR-GQ10T-D/△/▲/N

Stainless Steel
GQ10T-D/△/▲/S


Black Plated Brass
GQ10T-D/△/▲/A



Nickel Plated Brass
MR-GQ10T-D/Y/△/▲/N

Stainless Steel
GQ10T-D/Y/△/▲/S


Black Plated Brass
GQ10T-D/Y/△/▲/A



Nickel Plated Brass
MR-GQ10G-D/△/▲/N

Stainless Steel
GQ10G-D/△/▲/S


Black Plated Brass
GQ10G-D/△/▲/A



Nickel Plated Brass
MR-GQ10G-D/Y/△/▲/N

Stainless Steel
GQ10G-D/Y/△/▲/S

Black Plated Brass
GQ10G-D/Y/△/▲/A



- ⊙ Lamp Color(△): R G Y B W
- ⊙ Lamp Voltage(▲): 6V, 12V, 24V, 110V(with external resistor), 220V(with external resistor)
- ⊙ Mounting Hole Diameter: Φ10mm
- ⊙ Lamp type: LED
- ⊙ Rated Current: 2mA~20mA
- ⊙ Mounting Nut Torque: About 0.1Nm
- ⊙ Panel Thickness: 6mm Max.
- ⊙ Terminal: Solder Lug (2.8x0.5mm) / Wire Leads 150mm
- ⊙ Soldering Temperature: 320°C 3s
- ⊙ Body Material: Nickel Plated Brass / Black plated Brass / Stainless Steel
- ⊙ Lens Material: Epoxy(UV resistant can be customized)
- ⊙ Base: PA
- ⊙ IP Rating: IP67; IK06(Flat round type only)
- ⊙ RoHS can be Customized

MR-GQ10 Indicator Specifications

PART NUMBERS ON THIS DRAWING

MR-GQ10G-D MR-GQ10T-D

10 MM METAL INDICATOR LIGHT

MR-GQ10 SERIES

Micro-Ray

PART NO

MR-GQ10

DWG NO

MR-GQ10

UNITS: mm

SCALE: NTS - DO NOT SCALE

SHEET

1 OF 1

REV

A

SIZE

A4

DATE

2026-09-22