


Nickel Plated Brass
MR-GQ12T-D/△/▲/N

Stainless Steel
GQ12T-D/△/▲/S


Black Plated Brass
GQ12T-D/△/▲/A



Nickel Plated Brass
MR-GQ12T-D/Y/△/▲/N

Stainless Steel
GQ12T-D/Y/△/▲/S


Black Plated Brass
GQ12T-D/Y/△/▲/A



Nickel Plated Brass
MR-GQ12G-D/△/▲/N

Stainless Steel
MR-GQ12G-D/△/▲/S


Black Plated Brass
MR-GQ12G-D/△/▲/A



Nickel Plated Brass
MR-GQ12G-D/Y/△/▲/N

Stainless Steel
MR-GQ12G-D/Y/△/▲/S

Black Plated Brass
MR-GQ12G-D/Y/△/▲/A



- ☉ Lamp Color(△): **R** **G** **Y** **B** **W**
- ☉ Lamp Voltage(▲): 6V, 12V, 24V, 110V(with external resistor), 220V(with external resistor)

MR-GQ12 Indicator Specifications

- ☉ Mounting Hole Diameter: Φ12mm
- ☉ Lamp type: LED
- ☉ Rated Current: 2mA~20mA
- ☉ Mounting Nut Torque: About 0.1Nm
- ☉ Panel Thickness: 6mm Max.
- ☉ Terminal: Solder Lug (2.8x0.5mm) / Wire Leads 150mm
- ☉ Soldering Temperature: 320°C 3s
- ☉ Body Material: Nickel Plated Brass / Black plated Brass / Stainless Steel
- ☉ Lens Material: Epoxy(UV resistant can be customized)
- ☉ Base: PA
- ☉ IP Rating: IP67; IK06(Flat round type only)
- ☉ RoHS can be Customized

PART NUMBERS ON THIS DRAWING
MR-GQ12G-D MR-GQ12T-D

12 MM METAL INDICATOR LIGHT MR-GQ12 SERIES

Micro-Ray

PART NO **MR-GQ12**

DWG NO **MR-GQ12**

UNITS: mm SCALE: NTS - DO NOT SCALE

SHEET
1 OF 1

REV
A

SIZE
A4

DATE
2026-09-22