


Nickel Plated Brass
GQ19T-D/△/▲/N

Stainless Steel
GQ19T-D/△/▲/S


Black Plated Brass
GQ19T-D/△/▲/A



Nickel Plated Brass
GQ19G-D/△/▲/N

Stainless Steel
GQ19G-D/△/▲/S


Black Plated Brass
GQ19G-D/△/▲/A



Nickel Plated Brass
GQ19T-D/L/△/▲/N

Stainless Steel
GQ19T-D/L/△/▲/S


Black Plated Brass
GQ19T-D/L/△/▲/A



Nickel Plated Brass
GQ19G-D/L/△/▲/N

Stainless Steel
GQ19G-D/L/△/▲/S

Black Plated Brass
GQ19G-D/L/△/▲/A



- ⊙ Lamp Color(△): **R** **G** **Y** **B** **W**
- ⊙ Lamp Voltage(▲): 6V, 12V, 24V, 110V(with external resistor), 220V(with external resistor)
- ⊙ Mounting Hole Diameter: Φ19mm
- ⊙ Lamp type: LED
- ⊙ Rated Current: 2mA~20mA
- ⊙ Mounting Nut Torque: About 0.1Nm
- ⊙ Panel Thickness: 6mm Max.
- ⊙ Terminal: Solder Lug (2.8x0.5mm) / Screw Terminals
- ⊙ Soldering Temperature: 320°C 3s
- ⊙ Body Material: Nickel Plated Brass / Black plated Brass / Stainless Steel
- ⊙ Lens Material: Epoxy(UV resistant can be customized)
- ⊙ Base: PA
- ⊙ IP Rating: IP67; IK06(Flat round type only)
- ⊙ RoHS can be Customized

MR-GQ19 Indicator Specifications

PART NUMBERS ON THIS DRAWING
MR-GQ19G-D MR-GQ19T-D

19 MM METAL INDICATOR LIGHT		Micro-Ray	
MR-GQ19-IND SERIES			
PART NO	MR-GQ19-IND		
DWG NO	MR-GQ19-IND	SHEET 1 OF 1	REV A
UNITS: mm	SCALE: NTS - DO NOT SCALE	SIZE A4	DATE 2026-09-22