


Nickel Plated Brass  
GQ8T-D/ $\Delta$ / $\blacktriangle$ /N

Stainless Steel  
GQ8T-D/ $\Delta$ / $\blacktriangle$ /S


Black Plated Brass  
GQ8T-D/ $\Delta$ / $\blacktriangle$ /A



Nickel Plated Brass  
MR-GQ8T-D/Y/ $\Delta$ / $\blacktriangle$ /N

Stainless Steel  
GQ8T-D/Y/ $\Delta$ / $\blacktriangle$ /S


Black Plated Brass  
GQ8T-D/Y/ $\Delta$ / $\blacktriangle$ /A



Nickel Plated Brass  
MR-GQ8G-D/ $\Delta$ / $\blacktriangle$ /N

Stainless Steel  
GQ8G-D/ $\Delta$ / $\blacktriangle$ /S


Black Plated Brass  
GQ8G-D/ $\Delta$ / $\blacktriangle$ /A



Nickel Plated Brass  
MR-GQ8G-D/Y/ $\Delta$ / $\blacktriangle$ /N

Stainless Steel  
GQ8G-D/Y/ $\Delta$ / $\blacktriangle$ /S

Black Plated Brass  
GQ8G-D/Y/ $\Delta$ / $\blacktriangle$ /A



- ⊙ Lamp Color( $\Delta$ ): **R** **G** **Y** **B** **W**
- ⊙ Lamp Voltage( $\blacktriangle$ ): 6V, 12V, 24V, 110V(with external resistor), 220V(with external resistor)

- ⊙ Mounting Hole Diameter:  $\Phi 8\text{mm}$
- ⊙ Lamp type: LED
- ⊙ Rated Current: 2mA~20mA
- ⊙ Mounting Nut Torque: About 0.1Nm
- ⊙ Panel Thickness: 6mm Max.
- ⊙ Terminal: Solder Lug (2.8x0.5mm) / Wire Leads 150mm
- ⊙ Soldering Temperature: 320°C 3s

- ⊙ Body Material: Nickel Plated Brass / Black plated Brass / Stainless Steel
- ⊙ Lens Material: Epoxy(UV resistant can be customized)
- ⊙ Base: PA
- ⊙ IP Rating: IP67; IK06(Flat round type only)
- ⊙ RoHS can be Customized

#### MR-GQ8 Indicator Specifications

PART NUMBERS ON THIS DRAWING

MR-GQ8G-D MR-GQ8T-D

### 8 MM METAL INDICATOR LIGHT

MR-GQ8 SERIES

# Micro-Ray

PART NO

MR-GQ8

DWG NO

MR-GQ8

UNITS: mm

SCALE: NTS - DO NOT SCALE

SHEET

1 OF 1

REV

A

SIZE

A4

DATE

2026-09-22