



# AK2.5-TN-TG

DIN Rail Terminal Blocks > Spring Clamp Connection

Date:2026-09-11Version:1.1



The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.  
The final product is made according to engineering drawing.

## Product Description

300V, 16A, Beige (default)

## General information

|                   |                                                      |
|-------------------|------------------------------------------------------|
| Short description | DIN Rail terminal blocks, Disconnect terminal blocks |
| Category          | Disconnect terminal blocks                           |
| Color             | Beige (default)                                      |
| Connection method | Spring Clamp Connection                              |
| Type of locking   | Rail Mounting                                        |
| Length (mm)       | 72.6                                                 |
| Width (mm)        | 5.1                                                  |
| Height (mm)       | 36.7                                                 |
| Level             | Single level                                         |
| Connection points | 3                                                    |

## Material information

|                                              |    |
|----------------------------------------------|----|
| Insulation material                          | PA |
| Insulation material group                    | I  |
| Flame retardant rating , compliant with UL94 | V0 |

Insulation resistance

 $\geq 500\text{M}\Omega$  at DC 500V

## Connection data-IEC

|                                                                                                         |         |
|---------------------------------------------------------------------------------------------------------|---------|
| Rated voltage (V)                                                                                       | 400     |
| Rated current (A)                                                                                       | 21      |
| Rated voltage (III/3)(V)                                                                                | 400     |
| Rated impulse voltage (II/2)(KV)                                                                        | 6       |
| Rated impulse voltage (III/2)(KV)                                                                       | 6       |
| Rated impulse voltage (III/3)(KV)                                                                       | 6       |
| Conductor cross section solid. min (mm <sup>2</sup> )                                                   | 0.2     |
| Conductor cross section solid.max (mm <sup>2</sup> )                                                    | 4       |
| Conductor cross section stranded. min (mm <sup>2</sup> )                                                | 0.2     |
| Conductor cross section stranded. max (mm <sup>2</sup> )                                                | 2.5     |
| Conductor cross section flexible, with min ferrule without plastic sleeve (mm <sup>2</sup> )            | 0.25    |
| Conductor cross section flexible, with max ferrule without plastic sleeve (mm <sup>2</sup> )            | 2.5     |
| Conductor cross section flexible, with min ferrule with plastic sleeve (mm <sup>2</sup> )               | 0.25    |
| Conductor cross section flexible, with max ferrule with plastic sleeve (mm <sup>2</sup> )               | 2.5     |
| 2 conductors with same cross section flexible, min twin ferrules with plastic sleeve (mm <sup>2</sup> ) | 0.5     |
| 2 conductors with same cross section flexible, max twin ferrules with plastic sleeve (mm <sup>2</sup> ) | 0.5     |
| Slotted screwdriver size (Blade thickness x Width)(mm)                                                  | 0.6x3.5 |
| Stripping Length (mm)                                                                                   | 10      |
| Mounting rail                                                                                           | TS-35   |
| End cover plate required                                                                                | YES     |
| Grounding connections                                                                                   | NO      |

## Connection data-UL

|                                   |     |
|-----------------------------------|-----|
| Rated voltage (UL/CUL Group B)(V) | 300 |
| Rated current (UL/CUL Group B)(A) | 16  |
| Rated voltage (UL/CUL Group C)(V) | 300 |
| Rated current (UL/CUL Group C)(A) | 16  |
| Rated voltage (UL/CUL Group D)(V) | 600 |
| Rated current (UL/CUL Group D)(A) | 5   |

|                                                  |    |
|--------------------------------------------------|----|
| Min. solid wire connection (AWG) acc. to UL/CUL  | 28 |
| Max. solid wire connection AWG acc. to UL/CUL    | 12 |
| Min. stranded wire connection AWG acc. to UL/CUL | 28 |
| Max. stranded wire connection AWG acc. to UL/CUL | 12 |

## Environment & Safety

|                                         |     |
|-----------------------------------------|-----|
| Back of the hand protection (YES or NO) | YES |
| Finger protection (YES or NO)           | YES |
| Operating temperature. max (°C)         | 120 |
| Operating temperature. min (°C)         | -40 |

## UL Recognized

|                            |       |
|----------------------------|-------|
| Wire Range (Group B)(AWG)  | 28~12 |
| Rated voltage (Group B)(V) | 300   |
| Rated current (Group B)(A) | 16    |
| Wire Range (Group C)(AWG)  | 28~12 |
| Rated voltage (Group C)(V) | 300   |
| Rated current (Group C)(A) | 16    |
| Wire Range (Group D)(AWG)  | 28~12 |
| Rated voltage (Group D)(V) | 600   |
| Rated current (Group D)(A) | 5     |

## CUL Recognized


|                            |       |
|----------------------------|-------|
| Wire Range (Group B)(AWG)  | 28~12 |
| Rated voltage (Group B)(V) | 300   |
| Rated current (Group B)(A) | 16    |
| Wire Range (Group C)(AWG)  | 28~12 |
| Rated voltage (Group C)(V) | 300   |
| Rated current (Group C)(A) | 16    |
| Wire Range (Group D)(AWG)  | 28~12 |
| Rated voltage (Group D)(V) | 600   |
| Rated current (Group D)(A) | 5     |

## VDE Approval

|                               |         |
|-------------------------------|---------|
| Wire Range (mm <sup>2</sup> ) | 0.2~2.5 |
|-------------------------------|---------|

|                   |     |
|-------------------|-----|
| Rated voltage (V) | 400 |
| Rated current (A) | 21  |

## Drawings



## Approvals

