

IT32 Intel(R) Core(TM) i5 x86 Embedded Motherboard

Manufacturer part number: IT32 | Embedded Board



Explore Winmate IT32, an industrial embedded board featuring Intel(R) Core(TM) i5, 3.5-inch form factor for OEM equipment design and embedded control.

System Specification	
Processor	Intel Core i5-1135G7 2.4GHz (up to 4.2GHz)
Memory	4GB(Default), 8GB (Optional), 16GB (Optional), 32GB (Optional)
Storage	128GB SSD(Default), 256GB SSD (Optional), 512GB SSD (Optional), 1TB (Optional), 2TB (Optional), 4TB, 1 x SATA III for 2.5" SSD/HDD up to 2TB (Optional)
Ethernet controller	2 x Intel(R) Ethernet Controller
Security	TPM 2.0
Operating System	Windows 11 IoT Enterprise (64 bit) (Optional), Windows 11 Pro 64 bit (Optional), Linux Ubuntu 22.04(Do not support Wake on Touch) (Optional)
WLAN	Support (Optional)
BT	Support (Optional)
IO Ports	
USB Port	2 x USB3.2 Gen2x1 (Type-A)
Serial Port	1 x RS232/422/485 (Default RS232)
LAN	2 x 2.5 Giga LAN RJ45 Connector
Video	1 x HDMI 2.0 (Optional)
Expansion Port	1 x M.2 2280 M-Key Slot (for NVME SSD), 1 x M.2 2230 E-Key Slot (for Wi-Fi module)
Power Input	1 x 12V DC, 2.5? DC jack
Internal IO Ports	
Power input	1 x 6pin(1x6) for 12V DC in
Power output	1 x 2pin(1x2) blue wafer for 3.3V DC out, 1 x 2pin(1x2) red wafer for 5V DC out , 1 x 2pin(1x2) yellow wafer for 12V DC out
USB	2 x 8pin(2x4) for 4 x USB 2.0
Serial port	3 x 10pin(2x5) for RS232
Display	1 x 40pin DF13 connector for LVDS (Default), 1 x 30pin DF13 connector for eDP (Optional)
Backlight	1 x 7pin(1x7) for panel backlight
SATA	1 x SATA III, 1 x 8pin(2x4) for SATA power
DIDO	1 x 14pin(2x7) for Digital input/output

VR	1 x 3pin(1x3) for Digital panel backlight brightness control, 1 x 3pin(1x3) VR/Software brightness switch jumper, 1 x 3pin(1x3) PWM/DC brightness switch jumper, 1 x 3pin(1x3) 3.3V/5V PWM Level switch jumper
Fan	1 x 3pin(1x3) for CPU Fan
OSD	1 x 10pin(2x5) for OSD control
Speaker	2 x 2pin(1x2) for Speaker
Backup battery	1 x 2pin(1x2) for RTC battery
Audio	1 x 12pin(2x6) for Line in/Line out/ Mic in
Certification	
Certification	CE, FCC
Mechanical	
Dimension	146 x 102 mm
Environment	
Operating Humidity	10% to 95% RH, Non-Condensing
Operating Temperature	0 deg C to 60 deg C
Storage Temperature	-40 deg C to 70 deg C
Accessory	
Accessory	1 x Installation Guide
Optional Accessory	1 x SATA cable (94H007Z070K0) (Optional), 1 x SATA Power cable (94HE08Z150E0) (Optional), 1 x COM cable (94G309E100E1) (Optional), 1 x 2-Port USB 2.0 Type A cable (94E808E080K0) (Optional), 1 x 12V 120W Adapter (922D120W12V5) (Optional), 1 x Power cord (Varies by country) (Optional), 1 x CPU Heatspreader (98K000A000N3) (Optional), 1 x Membrane (98K000A000N1) (Optional), 2 x Speaker (612620000007) (Optional)
Power	
Power Rating	12V DC in