

ITMH100 Intel(R) Core(TM) i5-1135G7 M Series Box PC

Manufacturer part number: ITMH100 | Box PC / Waterproof Rugged PC IP65



Explore Winmate ITMH100, an industrial embedded computer featuring Intel(R) Core(TM) i5-1135G7 for industrial automation and embedded systems.

System Specification	
Processor	Intel Core i5-1135G7 2.4GHz (up to 4.2GHz)
Memory	2x, 4GB (Default), 8GB (Optional), 16GB (Optional), 32GB (Optional)
Storage	1 x M.2 2280 NVMe SSD, 128GB up to 512GB (Default), 2 x 2.5" Removable 256GB SSD up to 512GB (Optional)
Ethernet controller	Intel(R) Ethernet Controller I211-AT +, Intel(R) Ethernet Connection I219-LM
Security	Trusted Platform Module (TPM) 2.0
Operating System	Windows 11 IoT Enterprise (64 bit) (Optional), Windows 11 Pro 64 bit (Optional), Linux Ubuntu 22.04(Do not support Wake on Touch) (Optional)
WLAN	Support (Optional)
BT	Support (Optional)
Expansion Port	Modular Design for easy service in the field
Mechanical	
Dimension	276 x 207 x 60 mm
Weight	3.0 kg
Mounting	VESA mount
Enclosure	Metal Housing
Cooling System	Fanless Design
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	0 deg C to 50 deg C
Storage Temperature	-10 deg C to 60 deg C
Certification	
Certification	CE, FCC
IO Ports	
USB Port	4 x USB 3.2 Gen.1 (Type-A)
Serial Port	2 x RS232/422/485 (Default RS232)
LAN	2 x Giga LAN RJ45 Connector
Video	1 x DP1.4 (Default), 1 x HDMI 2.0 (Optional)

Audio	1 x Audio Combo Connector (Mic in / Line Out)
Expansion Port	1 x mPCIe slot, 1 x PCIe x16 slot (x4 signal)(module max size:180x121mm), 1 x M.2 2230 Key E slot for WiFi , 1 x M.2 2280 Key M slot for NVMe SSD, Swappable 2.5" HDD/SSD Bay Slot
Indicator	1 x LED Indicator for storage
Power Input	1 x 9~29V DC, 3-Pin Terminal Block
Control	
Button	1 x Power Button with LED Indicator, 1 x Reset Button
Accessory	
Accessory	100~240V AC to DC Adapter, Power Cord, Open Wire Cable with terminal block connector, VESA screws
Power	
Power Rating	9V~29V DC with protection fuse
Adapter	12V 84W
Consumption	45W~55W