



L140AD-3 13.3-inch Ultra Rugged Laptop with Intel(R) Core(TM) i5-1235U

Manufacturer part number: L140AD-3 | Rugged Laptop



Explore Winmate L140AD-3, an industrial computer solution featuring Intel(R) Core(TM) i5-1235U, 13.3-inch display with 1920x1080 resolution for industrial...

Display	
Size	13.3 inches
Resolution	1920x1080
Type	Projected Capacitive Multi Touch
Panel Brightness	500.0 nits
Contrast Ratio	1000:1
View Angles	89,89,89,89
Bonding	Optical Bonding for Sunlight Viewability
System Specification	
Processor	Intel Core i5-1235U (up to 4.4GHz) (Default), Intel Core 5 120U (up to 5GHz)(Optional)
Memory	8GB (Default), 16GB (Optional), 32GB (Optional)
Storage	128GB SSD (Default), 256GB SSD (Optional), 512GB SSD (Optional), 1TB SSD (Optional), 2TB SSD (Optional), 2nd storage available with up to 2TB SSD (Optional)
Smart Card Reader	Smart Card Reader (Mutually exclusive with 2nd LAN)
Security	Trusted Platform Module (TPM) 2.0, Kensington Lock
Operating System	Windows 11 IoT Enterprise LTSC (64 bit) (Default), Windows 10 IoT Enterprise LTSC (64 bit) (Optional)
WLAN	Support
BT	Support
WWAN	4G LTE (Optional), 5G (Optional)
GNSS	GPS, GLONASS
RFID	HF RFID reader 13.56 MHz (Optional)
Fingerprint Scanner	Fingerprint scanner (Optional)
Camera	
Front Camera	2MP front camera
Mechanical	
Dimension	340 x 230 x 38 mm
Weight	2.8 kg
Cooling System	Fan Design

IO Ports	
USB Port	1 x USB 3.0 (Type C), 3 x USB 3.0 (Type A) (One USB-A is mutually exclusive with 2nd LAN)
Serial Port	1 x DB9 (RS232 / RS422 / RS485, switchable with optional software)
LAN	1 x RJ45-10/100/1000 GigaLAN port (Default), 2nd LAN (Mutually exclusive with one USB-A & Smart Card Reader) (Optional)
Video	1 x HDMI 4K Output (Optional)
Audio	1 x Audio combo 3.5mm audio combo jack, Dual Digital Mic With Noise Cancellation, Dual Speaker
SD Card Slot	1 x Micro SDXC Slot
SIM Card Slot	1 x Nano SIM card slot
Indicator	3x LED Indicator for Power, Battery, Capslock status
Environment	
Operating Humidity	10% to 90% RH, non-condensing
Operating Temperature	-20 deg C to 60 deg C
Storage Temperature	-30 deg C to 70 deg C
Shock	USA: MILSTD810H Method 516.8 Procedure I, NATO: STANAG 4370/AECTP400 Edition 3 Method AECTP 402-Procedure I
Vibration	USA: MILSTD810H Method 514.8 Procedure I, NATO: STANAG 4370/AECTP400 Edition 3 Method AECTP 401-Procedure I
Drop	USA: MIL-STD-810H Method 516.8 Procedure IV, 4 ft, NATO: STANAG 4370/AECTP400 Edition 3 Method AECTP 404 - Procedure II, 4 ft
IP rating	IP65
EMC	USA:, MIL-STD-461G CE101, CE102, RE101, RE102, CS118 (Default), MIL-STD-461G CS101, CS114, CS115, CS116, RS101, RS103 (Optional), MIL-STD-461G RE102 Ground Army Grade, , NATO:, STANAG 4370/AECTP501 NCE01, NCE02, NRE01, NRE02, NCS12 (Optional), STANAG 4370/AECTP501 NCS01, NCS07, NCS08, NCS09, NRS01, NRS02 (Optional), STANAG 4370/AECTP501 NRE02-2 Land Environment (Optional)
TEMPEST	USA: NSA NSTISSAM TEMPEST/192 (Optional), NATO: SDIP27 (Optional)
Certification	
Certification	CE, FCC
Security Function	
SOTI MobiControl	SOTI MobiControl Compliance
Kensington Lock	Kensington Lock Support
Control	
Button	1 x Power, 2 x volume key,, 2 x Programmable Function Keys, QWERTY keyboard with RGB backlight
Power	
Battery	Hot-swappable 2 x 11.55V, typ. 3220 mAh Li-Ion Battery (3S1P)
Battery Operating Time	Standard Battery: 11 hours
Power Rating	19V DC
Adapter	100-240V, 50-60Hz / 19V DC
Accessory	
Accessory	Adapter and Power Cord, Standard Battery
Optional Accessory	Spare Battery (Optional), High Capacity Battery (Optional), Battery Charger (Optional), Vehicle Charger (Optional), Carry Bag (Optional)