



M101EK-ME 10.1" Healthcare Rugged Tablet PC with Intel(R) Celeron(R) N6211

Manufacturer part number: M101EK-ME | Healthcare Rugged Tablets



Explore Winmate M101EK-ME, a rugged tablet PC featuring Intel(R) Celeron(R) N6211, 10.1-inch display with 1920x1200 resolution, IP65...

Display	
Size	10.1 inches
Resolution	1920x1200
Type	Projected Capacitive Multi Touch
Panel Brightness	800.0 nits
Contrast Ratio	800:1
View Angles	85,85,85,85
Bonding	Optical Bonding for Sunlight Viewability
Viewability	Anti-Glare touch treatment
System Specification	
Processor	Intel Celeron N6211 @1.20 GHz (up to 3.00 GHz) (Default), Intel Pentium N6415 @1.20 GHz (up to 3.00 GHz) (Optional)
Memory	4GB (Default), 8GB (Optional)
Storage	128GB SSD, Additional storage available with micro SDXC card slot (Default), 256GB SSD (Optional), 512GB SSD (Optional)
Smart Card Reader	Add-on Smart Card Reader (Optional)
Security	Trusted Platform Module (TPM) 2.0, Kensington Lock
Operating System	Windows 11 IoT Enterprise LTSC (64 bit) (Default), Windows 10 IoT Enterprise LTSC (64 bit) (Optional)
WLAN	Support
BT	Support
WWAN	4G (Optional), 5G (Optional)
GNSS	GPS, GLONASS, Galileo, BeiDou
RFID	HF RFID 13.56 MHz reader (Optional), add-on UHF RFID Reader (Optional)
Sensors	Light sensor/ G-sensor / Gyro
Camera	
Front Camera	2MP Front Camera
Rear Camera	8MP Rear Camera with auto-focus and LED light
Mechanical	
Dimension	271.9 x 197.3 x 19.5 mm

Housing	Housing enhanced with antimicrobial properties
Weight	1.2 kg (2.65 lbs) with standard battery,, 1.4 kg (3.1 lbs) with optional high capacity battery
Cooling System	Fanless Design
IO Ports	
USB Port	1 x USB 3.0 (Type A), 1 x USB 3.0 (Type-C support Power Delivery 20V In)
Video	1 x Micro HDMI Output (Optional)
Audio	1 x Audio combo 3.5mm audio combo jack (Mic in or Line Out), Dual Digital Mic With Noise Cancellation, Dual Speaker
SD Card Slot	1 x Micro SD Card slot (Support SDXC)
SIM Card Slot	1 x SIM card slot
Expansion Port	1 x Expansion connector (Optional)
Indicator	4x LED Indicator for Power, Battery, HDD, RF status
Docking Connector	1 x 19-pin docking connector
Environment	
Operating Humidity	10% to 90% RH, non-condensing
Operating Temperature	0 to 35 deg C
Storage Temperature	-30 deg C to 70 deg C (-22 deg F to 158 deg F)
Shock	MIL-STD-810G Method 516.6 Procedure I
Vibration	MIL-STD-810G Method 514.6 Procedure I
Drop	MIL-STD-810G Method 516.6, 4 ft
IP rating	IP65
Certification	
Certification	CE, FCC, IEC/EN 60601-1, IEC/EN 60601-1-2, UL 60601-1
Control	
Button	1 x Power, 1 x Home, 2 x Volume,, 2 x Programmable Function Keys
Security Function	
SOTI MobiControl	SOTI MobiControl Compliance
Kensington Lock	Kensington Lock Support
Accessory	
Accessory	Adapter and Power Cord , Capacitive Stylus, Standard Battery
Optional Accessory	Desk Dock (Optional), Vehicle Dock (without VGA output) (Optional), Vehicle Cradle (Optional), Battery Charger (Optional), Smart Card Reader (Optional), High Capacity Battery (Optional), Hand Strap (Optional), VESA Mount Kit (Optional), Shoulder Strap (Optional), Carry Bag (Optional), Vehicle Charger (Optional)
Barcode Scanner	
Barcode Scanner	1D/2D barcode reader (Optional)
Power	
Battery	Hot-swappable 7.4V, typ. 5140 mAh Li-Polymer Battery (2S1P) (Default), 7.4V, typ. 10280 mAh Li-Polymer Battery (2S2P, Optional)
Battery Operating Time	Standard Battery: 8 hours
Power Rating	19V DC
Adapter	100-240V, 50-60Hz (19V DC)