

M140TGT 14" Intel(R) Core(TM) i5-1135G7 Industrial Rugged Tablet Integrated Smart Card Reader

Manufacturer part number: M140TGT | Windows Rugged Tablets



Explore Winmate M140TGT, a rugged tablet PC featuring Intel(R) Core(TM) i5-1135G7, 14-inch display with 1920x1080 resolution, IP65...

Display	
Size	14.0 inches
Resolution	1920x1080
Type	Projected Capacitive Multi Touch
Panel Brightness	700.0 nits
Contrast Ratio	800:1
View Angles	85,85,85,85
Bonding	Optical Bonding for Sunlight Viewability
System Specification	
Processor	Intel Core i5-1135G7 2.4GHz (up to 4.2GHz)
Memory	8GB (Default), 16GB (Optional), 32GB (Optional)
Storage	128GB SSD, Additional storage available with micro SDXC card slot (Default), 256GB SSD (Optional), 512GB SSD (Optional), 1TB SSD (Optional), 2TB SSD (Optional)
Smart Card Reader	Built-in Smart Card Reader, Comply with, ISO7816-1.2.3 T=1 and T=O protocol
Security	Trusted Platform Module (TPM) 2.0, Kensington Lock
Operating System	Windows 11 IoT Enterprise LTSC (64 bit) (Default), Windows 10 IoT Enterprise LTSC (64 bit) (Optional)
WLAN	Support
BT	Support
WWAN	4G LTE (Optional), 5G (Optional)
GNSS	GPS, GLONASS (Optional)
RFID	HF RFID reader 13.56 MHz (Optional)
Sensors	Light sensor/ G-sensor / Gyro
Camera	
Front Camera	2MP Front Camera
Rear Camera	8MP Rear Camera with auto-focus and LED light
Mechanical	
Dimension	341.91 x 224.67 x 25.4 mm

Weight	1.75 kg
Cooling System	Fan Design
IO Ports	
USB Port	2 x USB 3.0 (Type A), 1 x USB 3.0 (Type-C support Power Delivery 20V In)
LAN	1 x RJ45-10/100/1000 GigaLAN port
Video	1 x Micro HDMI (Optional)
Audio	1 x Audio combo 3.5mm audio combo jack, Dual Digital Mic With Noise Cancellation, Dual Speaker
SD Card Slot	1 x Micro SDXC slot
SIM Card Slot	1 x Nano SIM card slot
Indicator	4x LED Indicator for Power, Battery, HDD, RF status
Docking Connector	1 x 19-pin docking connector
Environment	
Operating Humidity	10% to 90% RH, non-condensing
Operating Temperature	-20 deg C to 60 deg C
Storage Temperature	-30 deg C to 70 deg C (-22 deg F to 158 deg F)
Shock	MIL-STD-810H Method 516.8 Procedure I
Vibration	MIL-STD-810H Method 514.8 Procedure I
Drop	MIL-STD-810H Method 516.8, 4 ft
IP rating	IP65
Certification	
Certification	CE, FCC
Security Function	
SOTI MobiControl	SOTI MobiControl Compliance
Kensington Lock	Kensington Lock Support
Control	
Button	1 x Power, 3 x function keys
Power	
Battery	Internal Battery: 10.8V typ. 2400 mAh Li-Ion Battery, Hot-swappable 11.4V, typ. 3500 mAh Li-Ion Re-chargeable Battery (3S1P), Hot-swappable 11.4V, typ. 4750 mAh Li-Ion Re-chargeable Battery (3S1P) (Optional)
Battery Operating Time	Standard. Battery: 8 hours, High Capacity Battery: 12 hours
Power Rating	19V DC
Adapter	100-240V, 50-60Hz / 19V DC
Accessory	
Accessory	Adapter and Power Cord, Standard Battery, Capacitive Stylus
Optional Accessory	Kickstand (Optional), Vehicle Charger (Optional), Battery Charger (Optional), Desk Dock (Optional), Carry Bag (Optional)