

# R08IAN3S-CHU1 8.4" Intel(R) Twin Lake N150 Chassis Panel PC

Manufacturer part number: R08IAN3S-CHU1 | Industrial Panel PCs (Resistive Touch)



Explore Winmate R08IAN3S-CHU1, an industrial panel PC featuring 8.4-inch display, IP65 for machine control and factory automation.

| Display               |                                                                                                                                                                                                  |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Size                  | 8.4 inches                                                                                                                                                                                       |
| Touch / Glass         | Resistive Touch Screen (Optional), Protection Glass Without Touch Function (Optional)                                                                                                            |
| Resolution            | 800x600                                                                                                                                                                                          |
| Panel Brightness      | 600.0 nits                                                                                                                                                                                       |
| Contrast Ratio        | 600:1                                                                                                                                                                                            |
| View Angles           | 75,75,60,70                                                                                                                                                                                      |
| Active Area           | 170.4x127.8 mm                                                                                                                                                                                   |
| System Specification  |                                                                                                                                                                                                  |
| Processor             | Intel(R) Processor N150 6M Cache, up to 3.60 GHz                                                                                                                                                 |
| Memory                | 8GB (Default), 16GB (Optional)                                                                                                                                                                   |
| Storage               | 128GB SSD (Default), 256GB SSD (Optional), 512GB SSD (Optional), 1TB (Optional), 2TB (Optional), 1 x SATA III for 2.5" SSD/HDD up to 2TB(Only available when NVME SSD is not present) (Optional) |
| Ethernet controller   | 2 x Intel(R) 2.5 Gigabit Ethernet Controller                                                                                                                                                     |
| Security              | TPM 2.0                                                                                                                                                                                          |
| Operating System      | Windows 11 IoT Enterprise (64 bit) (Optional), Windows 11 Pro 64 bit (Optional), Linux Ubuntu 24.04(Do not support Wake on Touch) (Optional)                                                     |
| Mechanical            |                                                                                                                                                                                                  |
| Dimension             | 236 x 190 x 60 mm                                                                                                                                                                                |
| Weight                | 2.2 kg                                                                                                                                                                                           |
| Mounting              | VESA mount                                                                                                                                                                                       |
| Enclosure             | Metal Housing                                                                                                                                                                                    |
| Cooling System        | Fanless Design                                                                                                                                                                                   |
| Environment           |                                                                                                                                                                                                  |
| Operating Humidity    | 10% to 90% RH, Non-Condensing                                                                                                                                                                    |
| Operating Temperature | 0 deg C to 50 deg C                                                                                                                                                                              |
| Storage Temperature   | -10 deg C to 60 deg C                                                                                                                                                                            |
| Certification         |                                                                                                                                                                                                  |
| Certification         | CE, FCC                                                                                                                                                                                          |

|                        |                                                                                       |
|------------------------|---------------------------------------------------------------------------------------|
| <b>IO Ports</b>        |                                                                                       |
| <b>USB Port</b>        | 2 x USB3.2 Gen1x1 (Type-A), 1 x USB 3.2 Gen 2x1 Type C connector,support DP Alt. mode |
| <b>Serial Port</b>     | 1 x RS232/422/485 (Default RS232), 1 x RS232                                          |
| <b>LAN</b>             | 2 x 2.5 Giga LAN RJ45 Connector                                                       |
| <b>Video</b>           | 1 x HDMI 2.0b (Optional)                                                              |
| <b>Audio</b>           | 2 x Speaker                                                                           |
| <b>Expansion Port</b>  | 1 x M.2 2230 E-Key Slot (for Wi-Fi module)                                            |
| <b>Indicator</b>       | 1 x LED Indicator for power, 1 x LED Indicator for storage                            |
| <b>Brightness Knob</b> | 1 x Brightness Adjustment Knob                                                        |
| <b>Power Input</b>     | 1 x 12V DC, 2.5? DC jack                                                              |
| <b>Control</b>         |                                                                                       |
| <b>Button</b>          | 1 x Power Button, 1 x Reset Button                                                    |
| <b>Accessory</b>       |                                                                                       |
| <b>Accessory</b>       | 100~240V AC to DC Adapter, Power Cord, VESA screws                                    |