



R08T200-VMU1 8.4" G-WIN Resistive Touch Display

Manufacturer part number: R08T200-VMU1 | G-WIN Series / IP67



Explore Winmate R08T200-VMU1, an industrial display featuring 8.4-inch display with 800x600 resolution, IP65 for industrial visualization and control rooms.

Display	
Size	8.4 inches
Touch / Glass	Resistive Touch Screen (Optional), Protection Glass Without Touch Function (Optional)
Resolution	800x600
Panel Brightness	600.0 nits
Contrast Ratio	600:1
View Angles	75,75,60,70
Display Color	262K Colors
Active Area	170.4x127.8 mm
Mechanical	
Dimension	277 x 219.5 x 59.6 mm
Weight	2.2 kg
Mounting	VESA Mount , Yoke Mount
Enclosure	Aluminum Housing
Cooling System	Fanless design
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	-10 deg C to 55 deg C
Storage Temperature	-30 deg C to 70 deg C
Shock	MIL-STD-810G Method 516.6 Procedure I (Optional)
Vibration	MIL-STD-810G Method 514.6 Procedure I
IP rating	Front IP65
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1x USB type-A for touch screen control (Optional)
Serial Port	1 x RS232 D-sub9 for touch screen control (Optional)
Video	1x VGA input (Default), 1x HDMI input (Optional)

Indicator	1 x LED Indicator for power, 1 x LED Indicator for status
Power Input	1 x 10~60V DC, 3-Pin Terminal Block
Control	
Button	1 x Power Button, 1 x Adjust up button, 1 x Adjust down button, 1 x ESC (Auto) button, 1 x Menu button
Accessory	
Accessory	Open Wire Cable with terminal block connector, External VGA cable, VESA screws
Optional Accessory	Yoke mount stand (Optional), 100~240V AC to DC 50W Adapter with power cord (Optional), External USB/COM cable for touchscreen control (Optional), External HDMI cable (Optional)