

R10IE3S-PPT2 10.4" Intel(R) Celeron(R) N6211 PP Series HMI Panel PC

Manufacturer part number: R10IE3S-PPT2 | HMI (P-CAP Touch)



Explore Winmate R10IE3S-PPT2, an HMI panel PC featuring Intel(R) Celeron(R) N6211, 10.4-inch display with 1024x768 resolution...

Display	
Size	10.4 inches
Touch / Glass	Projected Capacitive Multi Touch Screen
Resolution	1024x768
Panel Brightness	500.0 nits
Contrast Ratio	1000:1
View Angles	88,88,88,88
Active Area	210.4x157.8 mm
System Specification	
Processor	Intel(R) Celeron(R) N6211 (up to 3.0GHz)
Memory	4GB(Default), 8GB (Optional), 16GB (Optional)
Storage	128GB SSD(Default), 256GB SSD (Optional), 512GB SSD (Optional), 1TB (Optional), 2TB, 1 x SATA III for 2.5" SSD/HDD (Optional)
Ethernet controller	2 x Intel(R) Ethernet Controller
Security	TPM 2.0
Operating System	Windows 11 IoT Enterprise (64 bit) (Optional), Windows 11 Pro 64 bit (Optional), Windows 10 IoT Enterprise (64 bit) (Optional), Linux Ubuntu 22.04 (Optional)
WLAN	Support (Optional)
BT	Support (Optional)
Mechanical	
Dimension	284 x 252 x 55 mm
Cut out	262 x 220 mm
Weight	2.3 kg
Mounting	Panel mount (Default), VESA mount (Optional)
Enclosure	Metal Housing
Cooling System	Fanless Design
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	0 deg C to 50 deg C

Storage Temperature	-10 deg C to 60 deg C
IP rating	Front IP65
Certification	
Certification	CE, FCC
IO Ports	
USB Port	2 x USB3.2 Gen2x1 (Type-A)
Serial Port	1 x RS232/422/485 (Default RS232), 1 x RS232
LAN	2 x 2.5 Giga LAN RJ45 Connector
Video	1 x HDMI 2.0 (Optional)
Audio	2 x Speaker
Expansion Port	1 x M.2 2242 B-Key Slot (for SATA III SSD), 1 x M.2 2230 E-Key Slot (for Wi-Fi module)
Indicator	1 x LED Indicator for power, 1 x LED Indicator for storage
Brightness Knob	1 x Brightness Adjustment Knob
Power Input	1 x 12V DC, 2.5? DC jack
Control	
Button	1 x Power Button, 1 x Reset Button
Accessory	
Accessory	100~240V AC to DC Adapter, Power Cord, VESA screws, Mounting clips
Power	
Power Rating	12V DC
Adapter	12V 50W