



R10L100-65T2 10.4" IP65 Stainless Resistive Chassis Display

Manufacturer part number: R10L100-65T2 | Stainless Series



Explore Winmate R10L100-65T2, a chassis display featuring 10.4-inch display with 1024x768 resolution, IP65 for industrial visualization and control rooms.

Display	
Size	10.4 inches
Touch / Glass	Resistive Touch Screen (Optional), Protection Glass Without Touch Function (Optional)
Resolution	1024x768
Panel Brightness	350.0 nits
Contrast Ratio	1000:1
View Angles	88,88,88,88
Display Color	16.2M Colors
Active Area	210.4x157.8 mm
Mechanical	
Dimension	289 x 246 x 49.9 mm
Weight	3.81Kg
Mounting	VESA Mount , Yoke Mount
Enclosure	Stainless Housing
Cooling System	Fanless design
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	0 deg C to 45 deg C
Storage Temperature	-20 deg C to 60 deg C
IP rating	IP65
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1x M12 waterproof connector for touch screen control (Optional)
Serial Port	1 x M12 waterproof connector for touch screen control (Optional)
Video	1x M12 type connector for VGA input (Default), 1x waterproof DVI input (Optional), 1x waterproof connector for HDMI input (Optional)
Indicator	1 x LED Indicator for power, 1 x LED Indicator for status

Power Input	1 x M12 waterproof connector for 12V DC
Control	
Button	1 x Power Button, 1 x Adjust up button, 1 x Adjust down button, 1 x ESC (Auto) button, 1 x OK (Menu) button
Accessory	
Accessory	100~240V AC to DC Adapter with waterproof connector, Power Cord, External VGA cable with waterproof connector, Waterproof caps, Manual, VESA screws
Optional Accessory	Yoke mount stand (Optional), External HDMI cable with waterproof connector (Optional), External DVI cable with waterproof connector (Optional), External USB cable with waterproof connector for touchscreen control (Optional), External RS232 cable with waterproof connector for touchscreen control (Optional)
Power	
Power Rating	12V DC (M12 type)