



# R10L100-CHT2 10.4" Chassis Display

Manufacturer part number: R10L100-CHT2 | Chassis Display



Explore Winmate R10L100-CHT2, a chassis display featuring 10.4-inch display with 1024x768 resolution for industrial visualization and control rooms.

| Display               |                                                                                                                                |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Size                  | 10.4 inches                                                                                                                    |
| Touch / Glass         | Resistive Touch Screen (Default), Protection Glass w/o Touch Function (Optional), SAW Touch (Surface Acoustic Wave) (Optional) |
| Resolution            | 1024x768                                                                                                                       |
| Panel Brightness      | 350.0 nits                                                                                                                     |
| Contrast Ratio        | 1000:1                                                                                                                         |
| View Angles           | 88,88,88,88                                                                                                                    |
| Display Color         | 16.2M Colors                                                                                                                   |
| Active Area           | 210.4x157.8 mm                                                                                                                 |
| Environment           |                                                                                                                                |
| Operating Humidity    | 10% to 90% RH, Non-Condensing                                                                                                  |
| Operating Temperature | 0 deg C to 50 deg C                                                                                                            |
| Storage Temperature   | -10 deg C to 60 deg C                                                                                                          |
| Certification         |                                                                                                                                |
| Certification         | CE, FCC                                                                                                                        |
| IO Ports              |                                                                                                                                |
| USB Port              | 1 x USB for Touch Screen                                                                                                       |
| Video                 | 1 x VGA (Default), 1 x HDMI (Optional), 1 x DVI (Optional)                                                                     |
| Audio                 | Audio line in (3.5mm) (Optional), 2 x Speaker (Optional)                                                                       |
| Mechanical            |                                                                                                                                |
| Dimension             | 259.6 x 196.6 x 45 mm                                                                                                          |
| Mounting              | VESA Mount                                                                                                                     |
| Enclosure             | Metal Housing with Aluminum Bezel                                                                                              |
| Cooling System        | Fanless Design                                                                                                                 |
| Accessory             |                                                                                                                                |
| Accessory             | 1 x VGA cable, 1 x HDMI cable, 100~240V AC to DC Adapter, Power Cord, Manual, VESA screws(Varies by product)                   |
| Optional Accessory    | Remote Controller (Optional,Varies by product)                                                                                 |

|                     |                                     |
|---------------------|-------------------------------------|
| <b>Power</b>        |                                     |
| <b>Power Rating</b> | 12V DC in, 24V DC in (optional)     |
| <b>Control</b>      |                                     |
| <b>Button</b>       | 5 Keys: - , + , Power , Esc , Enter |