



R10L100-OFT2HB 10.4" Open Frame High Brightness Display

Manufacturer part number: R10L100-OFT2HB | Open Frame



Explore Winmate R10L100-OFT2HB, an open frame monitor featuring 10.4-inch display with 1024x768 resolution, IP65 for industrial visualization and control rooms.

Display	
Size	10.4 inches
Touch / Glass	Resistive Touch Screen (Optional), Protection Glass w/o Touch Function (Optional), SAW Touch (Surface Acoustic Wave) (Optional)
Resolution	1024x768
Panel Brightness	1000.0 nits
Contrast Ratio	1000:1
View Angles	88,88,88,88
Display Color	16.2M Colors
Active Area	210.4x157.8 mm
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	0 deg C to 50 deg C
Storage Temperature	-10 deg C to 60 deg C
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1 x USB for Touch Screen (Optional)
Video	1 x VGA (Default), 1 x HDMI (Optional), 1 x DVI (Optional)
Audio	Audio line in (3.5mm) (Optional), 2 x Speaker (Optional)
Accessory	
Accessory	1 x VGA cable, 1 x HDMI cable, 100~240V AC to DC Adapter, Power Cord, Manual, VESA screws(Varies by product)
Optional Accessory	Remote Controller (Optional,Varies by product)
Power	
Power Rating	12V DC in, 24V DC in (optional)
Control	
Button	5 Keys: - , + , Power , Esc , Enter