



R10L100-SPT2 10.4" IP65 Stainless PCAP Chassis Display

Manufacturer part number: R10L100-SPT2 | Stainless Series



Explore Winmate R10L100-SPT2, a chassis display featuring 10.4-inch display with 1024x768 resolution, IP65 for industrial visualization and control rooms.

Display	
Size	10.4 inches
Touch / Glass	Projected Capacitive Multi Touch Screen
Resolution	1024x768
Panel Brightness	350.0 nits
Contrast Ratio	1000:1
View Angles	88,88,88,88
Display Color	16.2M Colors
Active Area	210.4x157.8 mm
Mechanical	
Dimension	289 x 246 x 49.9 mm
Weight	3.8Kg
Mounting	VESA Mount , Yoke Mount
Enclosure	Stainless Housing
Cooling System	Fanless design
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	0 deg C to 45 deg C
Storage Temperature	-20 deg C to 60 deg C
IP rating	IP65
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1 x M12 waterproof connector for touch screen control
Video	1x M12 type connector for VGA input (Default), 1x waterproof connector for DVI input (Optional), 1x waterproof connector for HDMI input (Optional)
Indicator	1 x LED Indicator for power, 1 x LED Indicator for status
Control	

Button	1 x Power Button, 1 x Adjust up button, 1 x Adjust down button, 1 x ESC (Auto) button, 1 x OK (Menu) button
Accessory	
Accessory	100~240V AC to DC Adapter with waterproof connector, Power Cord, External USB cable with waterproof connector for touchscreen control, External VGA cable with waterproof connector, Waterproof caps, Manual, VESA screws
Optional Accessory	External HDMI cable with waterproof connector (Optional), External DVI cable with waterproof connector (Optional)
Power	
Power Rating	12V DC (M12 type)