



R10L600-CHP3TR 10.4" Chassis Transflective Display

Manufacturer part number: R10L600-CHP3TR | Chassis Display



Explore Winmate R10L600-CHP3TR, a chassis display featuring 10.4-inch display with 640x480 resolution for industrial visualization and control rooms.

Display	
Size	10.4 inches
Touch / Glass	Resistive Touch Screen (Default), Protection Glass w/o Touch Function (Optional), SAW Touch (Surface Acoustic Wave) (Optional)
Resolution	640x480
Panel Brightness	540.0 nits
Contrast Ratio	700:1
View Angles	80,80,80,60
Display Color	16.2M Colors
Active Area	211.2x158.4 mm
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	0 deg C to 50 deg C
Storage Temperature	-10 deg C to 60 deg C
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1 x USB for Touch Screen
Video	1 x VGA (Default), 1 x HDMI (Optional), 1 x DVI (Optional)
Audio	Audio line in (3.5mm) (Optional), 2 x Speaker (Optional)
Mechanical	
Dimension	260 x 200 x 45 mm
Mounting	VESA Mount
Enclosure	Metal Housing with Aluminum Bezel
Cooling System	Fanless Design
Accessory	
Accessory	1 x VGA cable, 1 x HDMI cable, 100~240V AC to DC Adapter, Power Cord, Manual, VESA screws(Varies by product)
Optional Accessory	Remote Controller (Optional,Varies by product)

Power	
Power Rating	12V DC in, 24V DC in (optional)
Control	
Button	5 Keys: - , + , Power , Esc , Enter