



R10MG3S-GCT2 10.4" ARM A78 + A55 G-WIN GC-Series Front IP65 PCAP Panel PC

Manufacturer part number: R10MG3S-GCT2 | G-WIN Series / IP67 Design



Explore Winmate R10MG3S-GCT2, an industrial panel PC featuring 10.4-inch display, IP65 for machine control and factory automation.

Display	
Touch / Glass	Projected Capacitive Multi Touch Screen
Size	10.4 inches
Resolution	1024x768
Panel Brightness	1000.0 nits
Contrast Ratio	1000:1
View Angles	88,88,88,88
Active Area	210.4x157.8 mm
System Specification	
Processor	ARM 2 x A78 2.0GHz + 4 x A55 2.0GHz
Memory	4GB LPDDR4
Storage	Onboard 32 GB
Operating System	Android 13 (Default), Linux Yocto 5.15.47 with QT 5.15 (Optional), Linux Ubuntu 22.04 (Optional)
WLAN	Support (Optional)
BT	Support (Optional)
Mechanical	
Dimension	252.41 x 197.8 x 36.4 mm
Cut out	230x178mm
Mounting	Panel mount, VESA mount
Enclosure	Aluminum
Cooling System	Fanless Design
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	0 deg C to 50 deg C
Storage Temperature	-20 deg C to 60 deg C
Shock	MIL-STD-810H Method 516.8 Procedure I
Vibration	MIL-STD-810H Method 514.8 Procedure I
IP rating	Front IP65

Certification	
Certification	CE, FCC
IO Ports	
USB Port	2 x USB 2.0 Type A , 1 x USB 2.0 Type C (OTG)
Serial Port	1 x RS232/422/485 (Default RS232)
LAN	1 x LAN 10/100/1000 Mbps
Video	1 x Micro HDMI Output (Optional)
SD Card Slot	1 x Micro SD card slot
Accessory	
Accessory	Quick Start Guide(Hardcopy) , AC Adapter 12V/50W, Power Cord, 3 Pin Terminal Block to DC Jack
Power	
Power Rating	12V DC with Terminal Block (Default), 24V (Optional), 9~36V (Optional)
Adapter	12V 50W
Control	
Button	1 x Power Button (Optional)