



R12L100-GSM2(HB) 12.1" G-WIN GS Series Display

Manufacturer part number: R12L100-GSM2(HB) | G-WIN Series / IP67



Explore Winmate R12L100-GSM2(HB), an industrial display featuring 12.1-inch display with 1024x768 resolution, IP65, MIL-STD-810F for industrial visualization...

Display	
Touch / Glass	Projected Capacitive Multi Touch Screen (Default), Protection Glass (Optional)
Size	12.1 inches
Resolution	1024x768
Panel Brightness	500 nits(Default), 1000 (Optional)
Contrast Ratio	1000:1
View Angles	89,89,89,89
Display Color	16.2M Colors
Active Area	245.76x184.32 mm
Environment	
Operating Humidity	10% to 95% RH
Operating Temperature	-15~55 deg C
Storage Temperature	-30 deg C to 60 deg C
Shock	40g for 11ms
Vibration	1.48/1.90/2.24 g rms for XYZ/ 5-500Hz
IP rating	IP65, Dustproof and Waterproof
Certification	
Certification	CE, FCC, Compliant with MIL-STD-810F/G for vibration / shock
IO Ports	
USB Port	1 x USB for Touch Screen
Video	1 x VGA
Mechanical	
Dimension	296.2 x 226.7 x 45.5 mm
Mounting	VESA Mount/ Panel Mount
Enclosure	Aluminum
Cooling System	Fanless Design
Accessory	

Accessory	Quick Start Guide(Hardcopy) , AC Adapter(For 7" Display only), M12 Power Cable(Not Supplied with 7" Display), VGA Cable, USB for Touch Cable, I/O Protective Cap x 3
Power	
Power Rating	9-36V DC (M12 type)
Control	
Button	5 Keys: - , + , Power , Esc , Enter