



R12L100-PCM2(HB) 12.1" Multi-Touch Chassis Industrial LCD Displays

Manufacturer part number: R12L100-PCM2(HB) | Multi-touch (P-CAP)



Explore Winmate R12L100-PCM2(HB), a chassis display featuring 12.1-inch display with 1024x768 resolution, IP65 for industrial visualization and control rooms.

Display	
Touch / Glass	Projected Capacitive Multi Touch Screen
Size	12.1 inches
Resolution	1024x768
Panel Brightness	500 nits(Default), 1000 (Optional)
Contrast Ratio	1000:1
View Angles	89,89,89,89
Display Color	16.2M Colors
Active Area	245.76x184.32 mm
Environment	
Operating Humidity	10% to 90% (Non-Condensing)
Operating Temperature	0~50 deg C
Storage Temperature	-30 deg C~70 deg C
Shock	MIL-STD-810G Method 516.6
Vibration	MIL-STD-810G Method 514.6
IP rating	Front IP65
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1 x USB for Touch Screen (Optional)
Video	1 x VGA (Default), 1 x HDMI (Optional), 1 x DVI (Optional)
Audio	Audio line in (3.5mm) (Optional), 2 x Speaker (Optional)
Mechanical	
Dimension	296.2 x 226.7 x 45.5 mm
Mounting	VESA mount
Enclosure	Metal
Cooling System	Fanless Design

Accessory	
Accessory	1 x VGA cable, 1 x HDMI cable, 100~240V AC to DC Adapter, Power Cord, Manual, VESA screws(Varies by product)
Optional Accessory	Remote Controller (Optional,Varies by product)
Power	
Power Rating	12V DC in, 24V DC in (optional)
Control	
Button	5 Keys: -, + , Power , Esc , Enter