



R12L600-CHM2OD 12.1" Resistive Touch Chassis Display

Manufacturer part number: R12L600-CHM2OD | Outdoor Display



Explore Winmate R12L600-CHM2OD, a chassis display featuring 12.1-inch display for industrial visualization and control rooms.

Display	
Size	12.1 inches
Touch / Glass	Resistive Touch Screen (Default), Protection Glass w/o Touch Function (Optional)
Resolution	1024x768
Panel Brightness	1000.0 nits
Contrast Ratio	700:1
View Angles	80,80,70,70
Display Color	16.2M Colors
Active Area	261.12x163.2 mm
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	-10 deg C to 60 deg C
Storage Temperature	-20 deg C to 70 deg C
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1 x USB for Touch Screen
Video	1 x VGA (Default), 1 x HDMI (Optional), 1 x DVI (Optional)
Audio	Audio line in (3.5mm) (Optional), 2 x Speaker (Optional)
Mechanical	
Dimension	290 x 230 x 45 mm
Weight	2 kg
Mounting	VESA Mount
Enclosure	Metal
Cooling System	Fanless Design
Accessory	
Accessory	1 x VGA cable, 1 x HDMI cable, 100~240V AC to DC Adapter, Power Cord, Manual, VESA screws(Varies by product)

Optional Accessory	Remote Controller (Optional,Varies by product)
Power	
Power Rating	12V DC in, 24V DC in (optional)
Control	
Button	5 Keys: - , + , Power , Esc , Enter