



R12L600-OFM2TR 12.1" Open Frame Transflective Display

Manufacturer part number: R12L600-OFM2TR | Open Frame



Explore Winmate R12L600-OFM2TR, an open frame monitor featuring 12.1-inch display with 1024x768 resolution, IP65 for industrial visualization and control rooms.

Display	
Size	12.1 inches
Touch / Glass	Resistive Touch Screen (Optional), Protection Glass w/o Touch Function (Optional), SAW Touch (Surface Acoustic Wave) (Optional)
Resolution	1024x768
Panel Brightness	600.0 nits
Contrast Ratio	700:1
View Angles	80,80,70,70
Display Color	16.2M Colors
Active Area	261.12x163.2 mm
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	0 deg C to 50 deg C
Storage Temperature	-10 deg C to 60 deg C
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1 x USB for Touch Screen (Optional)
Video	1 x VGA (Default), 1 x HDMI (Optional), 1 x DVI (Optional)
Audio	Audio line in (3.5mm) (Optional), 2 x Speaker (Optional)
Mechanical	
Dimension	300 x 250 x 40 mm
Mounting	VESA Mount/ Rear Mount
Enclosure	Metal
Cooling System	Fanless Design
Accessory	
Accessory	1 x VGA cable, 1 x HDMI cable, 100~240V AC to DC Adapter, Power Cord, Manual, VESA screws(Varies by product)

Optional Accessory	Remote Controller (Optional,Varies by product)
Power	
Power Rating	12V DC in, 24V DC in (optional)
Control	
Button	5 Keys: - , + , Power , Esc , Enter