

R15IE3S-GCC3(HB) 15" Intel(R) Celeron(R) N6211 G-WIN GC-Series Front IP65 PCAP Panel PC

Manufacturer part number: R15IE3S-GCC3(HB) | G-WIN Series / IP67 Design



Explore Winmate R15IE3S-GCC3(HB), an industrial panel PC featuring Intel(R) Celeron(R) N6211, 15-inch display with 1024x768 resolution...

Display	
Touch / Glass	Projected Capacitive Multi Touch Screen (Default), Anti-glare Coating (Optional)
Size	15.0 inches
Resolution	1024x768
Panel Brightness	300 nits(Default), 1000 (Optional)
Contrast Ratio	2000:1
View Angles	88,88,88,88
Active Area	304.1x228.1 mm
System Specification	
Processor	Intel(R) Celeron(R) N6211 (up to 3.0GHz)
Memory	4GB(Default), 8GB (Optional), 16GB (Optional)
Storage	128GB SSD(Default), 256GB SSD (Optional), 512GB SSD (Optional), 1TB (Optional), 2TB (Optional)
Ethernet controller	2 x Intel(R) Ethernet Controller
Security	TPM 2.0
Operating System	Windows 11 IoT Enterprise (64 bit) (Optional), Windows 11 Pro 64 bit (Optional), Windows 10 IoT Enterprise (64 bit) (Optional), Linux Ubuntu 22.04 (Optional)
Environment	
Operating Humidity	10% to 90% (Non-Condensing)
Operating Temperature	0~50 deg C
Storage Temperature	-30 deg C~70 deg C
Shock	MIL-STD-810G Method 516.6
Vibration	MIL-STD-810G Method 514.6
IP rating	Front IP65
Certification	
Certification	CE, FCC
IO Ports	
USB Port	2 x USB3.2 Gen2 x 1 (Type-A)

Serial Port	1 x RS232(Default)/422/485
LAN	2 x 2.5 Giga LAN RJ45 Connector
Video	1 x HDMI 2.0 (Optional)
Audio	2 x Speaker
Mechanical	
Dimension	363.4 x 277.9 x 45.2 mm
Mounting	VESA mount
Enclosure	Aluminum
Cooling System	Fanless Design
Accessory	
Accessory	User Manual(Hardcopy) , AC Adapter , Power Cable
Power	
Power Rating	12V DC input (Default), 9~36V DC input (Optional)
Control	
Button	1 x Power Button, 1 x Reset Button