



R15L100-67C3(HB) 15" G-WIN IP67 Series Display

Manufacturer part number: R15L100-67C3(HB) | G-WIN Series / IP67



Explore Winmate R15L100-67C3(HB), an industrial display featuring 15-inch display with 1024x768 resolution, IP67 for industrial visualization and control rooms.

Display	
Size	15.0 inches
Touch / Glass	Resistive Touch Screen Bonding With Panel (Default), Protection Glass Without touch function (Optional)
Resolution	1024x768
Panel Brightness	1000.0 nits
Contrast Ratio	2000:1
View Angles	88,88,88,88
Display Color	16.2M Colors
Active Area	304.1x228.1 mm
Mechanical	
Dimension	398 x 308 x 58 mm
Weight	4.2 kg
Mounting	VESA Mount , Yoke Mount
Enclosure	Aluminum Housing
Cooling System	Fanless design
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	-10 deg C to 55 deg C, -40 deg C to 70 deg C (with intelligent heater)
Storage Temperature	-30 deg C to 70 deg C
Shock	MIL-STD-810G Method 516.6 Procedure I
Vibration	MIL-STD-810G Method 514.6 Procedure I
IP rating	IP67
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1x M12 type connector for Touchscreen via USB signal
Serial Port	1 x M12 type connector for Touchscreen via RS232 signal (Optional)

Video	1x M12 type connector for VGA input (Default), 1x Waterproof connector for HDMI input (Optional)
Indicator	1 x LED Indicator for power, 1 x LED Indicator for status
Power Input	1 x M12 waterproof connector for 9~36V DC
Control	
Button	1 x Power Button, 1 x Adjust up button, 1 x Adjust down button, 1 x ESC (Auto) button, 1 x OK (Menu) button
Accessory	
Accessory	External open wire Power cable with waterproof connector, External USB cable with waterproof connector, External VGA cable with waterproof connector, Waterproof caps, VESA screws
Optional Accessory	Yoke mount stand (Optional), 100~240V AC to DC 50W Adapter with power cord (Optional), External COM cable with waterproof connector (Optional), External HDMI cable with waterproof connector (Optional)