



R15L100-67C3POD 15" PCAP Touch Chassis Display

Manufacturer part number: R15L100-67C3POD | Outdoor Display



Explore Winmate R15L100-67C3POD, a chassis display featuring 15-inch display with 1024x768 resolution, IP67 for industrial visualization and control rooms.

Display	
Size	15.0 inches
Touch / Glass	Projected Capacitive Multi Touch Screen Bonding With Panel (Default), Ture Flat Protection Glass Bonding With Panel (Optional)
Resolution	1024x768
Panel Brightness	1000.0 nits
Contrast Ratio	2000:1
View Angles	88,88,88,88
Display Color	16.2M Colors
Active Area	304.1x228.1 mm
Mechanical	
Dimension	379.4 x 278.4 x 58 mm
Weight	3.8 kg
Mounting	VESA mount
Enclosure	Aluminum Housing, Pre finish: Surtec 650, Type II, Class 3 Coating:, Polyester powder coating
Cooling System	Fanless Design
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	-10 deg C to 55 deg C, -25 deg C to 60 deg C (with intelligent heater)
Storage Temperature	-30 deg C to 70 deg C
Shock	MIL-STD-810G Method 516.6 Procedure I
Vibration	MIL-STD-810G Method 514.6 Procedure I
IP rating	IP67
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1 x M12 waterproof connector for 9–36V DC
Serial Port	1x M12 type connector for Touchscreen via USB signal

Video	1x M12 type connector for VGA input, 1x Waterproof connector for HDMI input
SD Card Slot	1 x M12 type connector for Touchscreen via RS232 signal (Optional), 1 x M12 type connector for RS232 Remote Control (Optional)
Indicator	1 x LED Indicator for power, 1 x LED Indicator for lock/unlock status
Control	
Button	1 x "Power" key to power on the device., 1 x "+" key to increase screen brightness., 1 x "-" key to decrease screen brightness., 1 x "Menu" key can Automatically or manually adjusts brightness of the display screen, 1 x Day / Night Mode button, 1 x LED indicator brightness adjustment button, 1 x Ambient Light sensor
Accessory	
Accessory	1 x External open wire Power cable with waterproof connector, 1 x External USB cable with waterproof connector for Touch, 1 x External VGA cable with waterproof connector, 1 x External HDMI cable with waterproof connector, 3 x Waterproof caps, VESA screws
Optional Accessory	100~240V AC to DC Adapter with power cord (Optional), External COM cable with waterproof connector (Optional)