



R15L100-67N1-NI 15" G-WIN Full IP67 NVIS Display

Manufacturer part number: R15L100-67N1-NI | Defence Display / NVIS Display



Explore Winmate R15L100-67N1-NI, an industrial display featuring 15-inch display with 1024x768 resolution, IP67, IP65 for defense operations and field command.

Display	
Touch / Glass	Projected Capacitive Multi Touch Screen Bonding With Panel (Default), Ture Flat Resistive Touch Screen Bonding With Panel (Optional), Ture Flat Protection Glass Bonding With Panel (Optional)
Size	15.0 inches
Resolution	1024x768
Panel Brightness	1000/NVIS nits
Contrast Ratio	2500:1
View Angles	88,88,88,88
Display Color	16.7M Colors
Active Area	304.1x228.1 mm
Mechanical	
Dimension	379.4 x 278.4 x 58 mm
Weight	3.8 kg
Mounting	VESA mount
Enclosure	Aluminum Housing, Pre finish: Surtec 650, Type II, Class 3 Coating:, Polyester powder coating
Cooling System	Fanless Design
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	-20 deg C to 60 deg C
Storage Temperature	-30 deg C to 70 deg C
Shock	MIL-STD-810G Method 516.6 Procedure I
Vibration	MIL-STD-810G Method 514.6 Procedure I
IP rating	IP67
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1x M12 type connector for Touchscreen via USB signal

Serial Port	1 x M12 type connector for Touchscreen via RS232 signal (Optional), 1 x M12 type connector for RS232 Remote Control (Optional)
Video	1x M12 type connector for VGA input, 1x Waterproof connector for HDMI input
Indicator	1 x LED Indicator for power, 1 x LED Indicator for lock/unlock status
Power Input	1 x M12 waterproof connector for 9~36V DC
Control	
Button	1 x "Power" key to power on the device., 1 x "+" key to increase screen brightness., 1 x "-" key to decrease screen brightness., 1 x "Menu" key can Automatically or manually adjusts brightness of the display screen, 1 x Day / Night Mode button, 1 x LED indicator brightness adjustment button, 1 x Ambient Light sensor
Accessory	
Accessory	External open wire Power cable with waterproof connector, External USB cable with waterproof connector for Touch, External VGA cable with waterproof connector, External HDMI cable with waterproof connector, Waterproof caps, VESA screws
Optional Accessory	100~240V AC to DC 50W Adapter with power cord (Optional), External COM cable with waterproof connector (Optional)