



R15L100-POC3 15" Multi-Touch Open Frame Display

Manufacturer part number: R15L100-POC3 | Multi-touch (P-CAP)



Explore Winmate R15L100-POC3, an open frame monitor featuring 15-inch display with 1024x768 resolution, IP65 for industrial visualization and control rooms.

Display	
Size	15.0 inches
Touch / Glass	Projected Capacitive Multi Touch Screen (Default), Anti-glare Coating (Optional)
Resolution	1024x768
Panel Brightness	300.0 nits
Contrast Ratio	2000:1
View Angles	88,88,88,88
Display Color	16.2M Colors
Active Area	304.1x228.1 mm
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	0 deg C to 50 deg C
Storage Temperature	-10 deg C to 60 deg C
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1 x USB for Touch Screen
Video	1 x VGA (Default), 1 x HDMI (Optional), 1 x DVI (Optional)
Audio	Audio line in (3.5mm) (Optional), 2 x Speaker (Optional)
Mechanical	
Dimension	358 x 276 x 42 mm
Cut out	360 x 278 mm
Weight	3.4 kg
Mounting	VESA Mount/ Panel Mount
Enclosure	Metal
Cooling System	Fanless Design
Accessory	

Accessory	1 x VGA cable, 1 x HDMI cable, 100~240V AC to DC Adapter, Power Cord, Manual, VESA screws(Varies by product)
Optional Accessory	Remote Controller (Optional,Varies by product)
Power	
Power Rating	12V DC in, 24V DC in (optional)
Control	
Button	5 Keys: - , + , Power , Esc , Enter