



R15L600-67C3ST 15" IP67 Stainless Resistive Chassis Display

Manufacturer part number: R15L600-67C3ST | Stainless Series



Explore Winmate R15L600-67C3ST, a chassis display featuring 15-inch display with 1024x768 resolution, IP67 for industrial visualization and control rooms.

Display	
Size	15 inches
Touch / Glass	Resistive Touch Screen Bonding With Panel (Default), Protection Glass Without touch function (Optional)
Resolution	1024x768
Panel Brightness	300 nits
Contrast Ratio	2000:1
View Angles	88,88,88,88
Display Color	16.2M Colors
Active Area	304.1x228.1 mm
Mechanical	
Dimension	383 x 310 x 57 mm
Mounting	VESA Mount , Yoke Mount
Enclosure	Stainless Housing
Cooling System	Fanless design
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	0 deg C to 45 deg C
Storage Temperature	-20 deg C to 60 deg C
IP rating	IP67
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1x M12 waterproof connector for touch screen control (Optional)
Serial Port	1 x M12 waterproof connector for touch screen control (Optional)
Video	1x M12 type connector for VGA input (Default), 1x waterproof DVI input (Optional), 1x waterproof connector for HDMI input (Optional)
Indicator	1 x LED Indicator for power, 1 x LED Indicator for status
Power Input	1 x M12 waterproof connector for 12V DC

Control	
Button	1 x Power Button, 1 x Adjust up button, 1 x Adjust down button, 1 x ESC (Auto) button, 1 x OK (Menu) button
Accessory	
Accessory	100~240V AC to DC Adapter with waterproof connector, Power Cord, External VGA cable with waterproof connector, External USB or RS232 cable with waterproof connector for touchscreen control, Waterproof caps, Manual, VESA screws
Optional Accessory	Yoke mount stand (Optional), External HDMI cable with waterproof connector (Optional), External DVI cable with waterproof connector (Optional)
Power	
Power Rating	12V DC (M12 type)