



R15L600-PCC3(HB) 15" Multi-Touch Chassis Display

Manufacturer part number: R15L600-PCC3(HB) | Multi-touch (P-CAP)



Explore Winmate R15L600-PCC3(HB), a chassis display featuring 15-inch display with 1024x768 resolution, IP65 for industrial visualization and control rooms.

Display	
Touch / Glass	Projected Capacitive Multi Touch Screen (Default), Protection Glass (Optional), Anti-glare Coating (Optional)
Size	15.0 inches
Resolution	1024x768
Panel Brightness	300 nits(Default), 1000 (Optional)
Contrast Ratio	2000:1
View Angles	88,88,88,88
Display Color	16.2M Colors
Active Area	304.1x228.1 mm
Environment	
Operating Humidity	10% to 90% (Non-Condensing)
Operating Temperature	0~50 deg C
Storage Temperature	-20 deg C~60 deg C
Shock	MIL-STD-810G Method 516.6
Vibration	MIL-STD-810G Method 514.6
IP rating	Front IP65
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1 x USB for Touch Screen
Video	1 x VGA (Default), 1 x HDMI (Optional), 1 x DVI (Optional)
Audio	Audio line in (3.5mm) (Optional), 2 x Speaker (Optional)
Accessory	
Accessory	1 x VGA cable, 1 x HDMI cable, 100~240V AC to DC Adapter, Power Cord, Manual, VESA screws(Varies by product)
Optional Accessory	Remote Controller (Optional,Varies by product)
Power	

Power Rating	12V DC in, 24V DC in (optional)
Control	
Button	5 Keys: -, +, Power, Esc, Enter