

R19L100-67N1-NI 19" G-WIN Full IP67 NVIS Display

Manufacturer part number: R19L100-67N1-NI | Defence Display / NVIS Display



Explore Winmate R19L100-67N1-NI, an industrial display featuring 19-inch display with 1280x1024 resolution, IP67, IP65 for defense operations and field command.

Display	
Touch / Glass	Projected Capacitive Multi Touch Screen Bonding with Panel
Size	19.0 inches
Resolution	1280x1024
Panel Brightness	1000/NVIS nits
Contrast Ratio	1000:1
View Angles	85,85,80,80
Display Color	16.7M Colors
Active Area	376.32x301.06 mm
Mechanical	
Dimension	474 x 410 x 111 mm
Cut out	462 x 386 mm
Weight	9.8 kg
Mounting	Panel mount (Default), VESA mount (Optional)
Enclosure	Aluminum Housing
Cooling System	Fanless Design
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	-20 deg C to 60 deg C
Storage Temperature	-30 deg C to 70 deg C
Shock	MIL-STD-810G Method 516.6 Procedure I
Vibration	MIL-STD-810G Method 514.6 Procedure I
IP rating	IP67
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1x M12 type connector for Touchscreen via USB signal

Serial Port	1 x M12 type connector for Touchscreen via RS232 signal (Optional)
Video	1x M12 type connector for VGA input (Default), 1x Waterproof connector for HDMI input (Optional)
Indicator	1 x LED Indicator for power, 1 x LED Indicator for status
Power Input	1 x M12 waterproof connector for 9~36V DC
Control	
Button	1 x Power Button, 1 x Adjust up button, 1 x Adjust down button, 1 x ESC (Auto) button, 1 x OK (Menu) button
Accessory	
Accessory	External open wire Power cable with waterproof connector, External USB cable with waterproof connector, External VGA cable with waterproof connector, Waterproof caps, Mounting clips, VESA screws
Optional Accessory	100~240V AC to DC 50W Adapter with power cord (Optional), External COM cable with waterproof connector (Optional), External HDMI cable with waterproof connector (Optional)