



R19L300-CHM2 19" Chassis Display

Manufacturer part number: R19L300-CHM2 | Chassis Display



Explore Winmate R19L300-CHM2, a chassis display featuring 19-inch display with 1280x1024 resolution for industrial visualization and control rooms.

Display	
Size	19.0 inches
Touch / Glass	Resistive Touch Screen (Default), Protection Glass w/o Touch Function (Optional), SAW Touch (Surface Acoustic Wave) (Optional)
Resolution	1280x1024
Panel Brightness	300.0 nits
Contrast Ratio	2000:1
View Angles	89,89,89,89
Display Color	16.7M Colors
Active Area	376.32x301.06 mm
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	0 deg C to 50 deg C
Storage Temperature	-10 deg C to 60 deg C
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1 x USB for Touch Screen
Video	1 x VGA (Default), 1 x HDMI (Optional), 1 x DVI (Optional)
Audio	Audio line in (3.5mm) (Optional), 2 x Speaker (Optional)
Mechanical	
Dimension	430 x 355 x 40 mm
Mounting	VESA Mount
Enclosure	Metal
Cooling System	Fanless Design
Accessory	
Accessory	1 x VGA cable, 1 x HDMI cable, 100~240V AC to DC Adapter, Power Cord, Manual, VESA screws(Varies by product)
Optional Accessory	Remote Controller (Optional,Varies by product)

Power	
Power Rating	12V DC in, 24V DC in (optional)
Control	
Button	5 Keys: - , + , Power , Esc , Enter