



# R19L300-OFM2 19" Open Frame Display

Manufacturer part number: R19L300-OFM2 | Open Frame



Explore Winmate R19L300-OFM2, an open frame monitor featuring 19-inch display with 1280x1024 resolution, IP65 for industrial visualization and control rooms.

| Display               |                                                                                                                                 |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Size                  | 19.0 inches                                                                                                                     |
| Touch / Glass         | Resistive Touch Screen (Optional), Protection Glass w/o Touch Function (Optional), SAW Touch (Surface Acoustic Wave) (Optional) |
| Resolution            | 1280x1024                                                                                                                       |
| Panel Brightness      | 300.0 nits                                                                                                                      |
| Contrast Ratio        | 2000:1                                                                                                                          |
| View Angles           | 89,89,89,89                                                                                                                     |
| Display Color         | 16.7M Colors                                                                                                                    |
| Active Area           | 376.32x301.06 mm                                                                                                                |
| Environment           |                                                                                                                                 |
| Operating Humidity    | 10% to 90% RH, Non-Condensing                                                                                                   |
| Operating Temperature | 0 deg C to 50 deg C                                                                                                             |
| Storage Temperature   | -10 deg C to 60 deg C                                                                                                           |
| Certification         |                                                                                                                                 |
| Certification         | CE, FCC                                                                                                                         |
| IO Ports              |                                                                                                                                 |
| USB Port              | 1 x USB for Touch Screen (Optional)                                                                                             |
| Video                 | 1 x VGA (Default), 1 x HDMI (Optional), 1 x DVI (Optional)                                                                      |
| Audio                 | Audio line in (3.5mm) (Optional), 2 x Speaker (Optional)                                                                        |
| Mechanical            |                                                                                                                                 |
| Dimension             | 445 x 355 x 56 mm                                                                                                               |
| Mounting              | VESA Mount/ Rear Mount                                                                                                          |
| Enclosure             | Metal                                                                                                                           |
| Cooling System        | Fanless Design                                                                                                                  |
| Accessory             |                                                                                                                                 |
| Accessory             | 1 x VGA cable, 1 x HDMI cable, 100~240V AC to DC Adapter, Power Cord, Manual, VESA screws(Varies by product)                    |

|                           |                                                |
|---------------------------|------------------------------------------------|
| <b>Optional Accessory</b> | Remote Controller (Optional,Varies by product) |
| <b>Power</b>              |                                                |
| <b>Power Rating</b>       | 12V DC in, 24V DC in (optional)                |
| <b>Control</b>            |                                                |
| <b>Button</b>             | 5 Keys: - , + , Power , Esc , Enter            |