



S101MT 10.1" Windows Rugged Tablet with Intel(R) Core(TM) Ultra 5 processor 125U

Manufacturer part number: S101MT | Windows Rugged Tablets



Explore Winmate S101MT, a rugged tablet PC featuring Intel(R) Core(TM) Ultra 5, 10.1-inch display with 1920x1200 resolution, IP65...

Display	
Size	10.1 inches
Resolution	1920x1200
Type	Projected Capacitive Multi Touch
Panel Brightness	800.0 nits
Contrast Ratio	800:1
View Angles	85,85,85,85
Bonding	Optical Bonding for Sunlight Viewability
Viewability	Anti-Glare touch treatment
Touch Mode	Support Hand/Rain, Stylus, Glove Mode
System Specification	
Processor	Intel Ultra 5 processor 125U 2.1 GHz (up to 4.3 GHz)
Memory	8GB (Default), 16GB (Optional), 32GB (Optional)
Storage	128GB SSD, Additional storage available with micro SDXC card slot (Default), 256GB SSD (Optional), 512GB SSD (Optional), 1TB SSD (Optional), 2TB SSD (Optional)
Security	Trusted Platform Module (TPM) 2.0, Kensington Lock
Operating System	Windows 11 IoT Enterprise LTSC (64 bit) (Default), Windows 10 IoT Enterprise LTSC (64 bit) (Optional)
WLAN	Support
BT	Support
WWAN	4G LTE (Optional), 5G (Optional)
GNSS	GPS, GLONASS
Sensors	Light sensor/ G-sensor / Gyro
Camera	
Front Camera	2MP Front Camera
Rear Camera	8MP Rear Camera with auto-focus and LED light
Mechanical	
Dimension	272 x 192 x 25 mm
Weight	1.1 kg
Cooling System	Fan Design

IO Ports	
USB Port	1 x USB 3.0 (Type A), 1 x USB 3.0 (Type-C support Power Delivery 20V In & ALT)
LAN	1 x RJ45-10/100/1000 GigaLAN port
Video	1 x Micro HDMI (Optional)
Audio	1 x Audio combo 3.5mm audio combo jack (Mic in or Line Out), Dual Mic Built-in Microphone, Single Speaker
SD Card Slot	1 x Micro SDXC slot
SIM Card Slot	1 x Nano SIM card slot
Expansion Port	1 x Expansion Connector for USB3.0 / UART (Optional)
Indicator	2x LED Indicator for Power, Battery
Docking Connector	1 x 19-pin docking connector
Environment	
Operating Humidity	10% to 90% RH, non-condensing
Operating Temperature	-20 deg C to 60 deg C
Storage Temperature	-30 deg C to 70 deg C (-22 deg F to 158 deg F)
Shock	MIL-STD-810H Method 516.8 Procedure I
Vibration	MIL-STD-810H Method 514.8 Procedure I
Drop	MIL-STD-810H Method 516.8, 4 ft
IP rating	IP65
Certification	
Certification	CE, FCC
Security Function	
SOTI MobiControl	SOTI MobiControl Compliance
Kensington Lock	Kensington Lock Support
Control	
Button	1 x Power, 2 x Programmable function Keys
Power	
Battery	11.4V, typ. 3500 mAh Li-Ion Re-chargeable Battery (3S1P), 11.4V, typ. 4750 mAh Li-Ion Re-chargeable Battery (3S1P) (Optional), Hot-Swap (Optional)
Battery Operating Time	Standard. Battery: 10.4 hours, High Capacity Battery: 14.8 hours
Power Rating	19V DC
Adapter	100-240V, 50-60Hz / 19V DC
Accessory	
Accessory	Adapter and Power Cord, Standard Battery
Optional Accessory	Vehicle Charger (Optional), Vehicle Dock (Optional), Desk Dock (Optional), Battery Charger (Optional), Hand Strap (Optional), Shoulder Strap (Optional), Carry Bag (Optional), Stylus (Optional)
Barcode Scanner	
Barcode Scanner	1D/2D barcode reader (Optional)