



W07IM3S-PCT1-POE 7" ARM A53 S Series HMI Panel PC

Manufacturer part number: W07IM3S-PCT1-POE | HMI (P-CAP Touch)



Explore Winmate W07IM3S-PCT1-POE, an HMI panel PC featuring 7-inch display with 1024x600 resolution, IP65 for machine control and factory automation.

Display	
Size	7.0 inches
Touch / Glass	Projected Capacitive Multi Touch Screen
Resolution	1024x600
Panel Brightness	320.0 nits
Contrast Ratio	1000:1
View Angles	75,75,75,70
Active Area	153.6x90 mm
System Specification	
Processor	ARM A53 (Quad Core 2.0GHz)
Memory	4GB LPDDR4
Storage	eMMC: Onboard 32 GB
Operating System	Android 11 (Upgradeable to Android 13) (Default), Linux Yocto 5.15.47 with QT 5.15 (Optional), Linux Ubuntu Server 22.04 (Optional)
WLAN	Support (Optional)
BT	Support (Optional)
RFID	HF RFID Reader 13.56 MHz (Optional)
Mechanical	
Dimension	189.4 x 145.4 x 40 mm
Cut out	175.5x131.5mm
Weight	1.0 kg
Mounting	Panel mount, VESA mount
Enclosure	Metal Housing
Cooling System	Fanless Design
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	0 deg C to 50 deg C
Storage Temperature	-20 deg C to 60 deg C
Shock	MIL-STD-810H Method 516.8 Procedure I

Vibration	MIL-STD-810H Method 514.8 Procedure I
IP rating	Front IP65
Certification	
Certification	CE, FCC
IO Ports	
USB Port	2 x USB 2.0 Type A , 1 x Micro USB 2.0 OTG
Serial Port	1 x RS232/422/485 (Default RS232)
LAN	1 x LAN 10/100/1000 Mbps
Video	1 x Micro HDMI Output (Optional)
Audio	1 x Speaker
SD Card Slot	1 x Micro SD card slot (Max to 32GB)
Accessory	
Accessory	100~240V AC to DC Adapter, Power Cord, Terminal Block to 2.5O Female Adapter Cable, Open Wire Cable with terminal block connector, VESA screws
Power	
Power Rating	12V DC with Terminal Block
Adapter	12V 50W
POE	PoE (PD): follows IEEE 802.3at (25 W)
Camera	
Front Camera	2MP Camera (Optional)