



W07L100-GSO1HB 7" G-WIN GS Series High Brightness Display

Manufacturer part number: W07L100-GSO1HB | G-WIN Series / IP67



Explore Winmate W07L100-GSO1HB, an industrial display featuring 7-inch display with 1024x600 resolution, IP65, MIL-STD-810F for industrial visualization and...

Display	
Touch / Glass	Projected Capacitive Multi Touch Screen (Default), Protection Glass (Optional)
Size	7.0 inches
Resolution	1024x0600
Panel Brightness	1000.0 nits
Contrast Ratio	800:1
View Angles	85,85,85,85
Display Color	16.7M Colors
Active Area	152.2144x85.92 mm
Environment	
Operating Humidity	10% to 95% RH
Operating Temperature	-15~55 deg C
Storage Temperature	-30 deg C to 60 deg C
Shock	40g for 11ms
Vibration	1.48/1.90/2.24 g rms for XYZ/ 5-500Hz
IP rating	IP65, Dustproof and Waterproof
Certification	
Certification	CE, FCC, Compliant with MIL-STD-810F/G for vibration / shock
IO Ports	
USB Port	1 x USB for Touch Screen
Video	1 x VGA
Mechanical	
Dimension	189.4 x 145.4 x 39.8 mm
Mounting	VESA mount (Default), Panel mount (Optional)
Enclosure	Metal Housing with Aluminum Bezel
Cooling System	Fanless Design
Accessory	

Accessory	Quick Start Guide(Hardcopy) , AC Adapter(For 7" Display only), M12 Power Cable(Not Supplied with 7" Display), VGA Cable, USB for Touch Cable, I/O Protective Cap x 3
Power	
Power Rating	12V DC (M12 type)
Control	
Button	5 Keys: - , + , Power , Esc , Enter