



W10L100-GSH2 10.1" G-WIN GS Series Display

Manufacturer part number: W10L100-GSH2 | G-WIN Series / IP67



Explore Winmate W10L100-GSH2, an industrial display featuring 10.1-inch display with 1280x800 resolution, IP65, MIL-STD-810F for industrial visualization and...

Display	
Size	10.1 inches
Touch / Glass	Projected Capacitive Multi Touch Screen (Default), Protection Glass (Optional), Anti-glare Coating (Optional)
Resolution	1280x800
Panel Brightness	350 nits(Default), 1000 (Optional)
Contrast Ratio	800:1
View Angles	85,85,85,85
Display Color	16.7M Colors
Active Area	216.96 x135.6 mm
Environment	
Operating Humidity	10% to 95% RH
Operating Temperature	-15 deg C to 55 deg C
Storage Temperature	-30 deg C to 60 deg C
Shock	40g for 11ms
Vibration	1.48/1.90/2.24 g rms for XYZ/ 5-500Hz
IP rating	Full IP65
Certification	
Certification	Compliant with MIL-STD-810F/G for vibration / shock, CE, FCC
IO Ports	
USB Port	1 x USB for Touch Screen
Video	1 x VGA
Mechanical	
Dimension	263.28 x 172 x 40.2 mm
Mounting	VESA Mount/ Panel Mount
Enclosure	Metal Housing with Aluminum Bezel
Cooling System	Fanless Design
Accessory	

Accessory	Quick Start Guide(Hardcopy) , AC Adapter(For 7" Display only), M12 Power Cable(Not Supplied with 7" Display), VGA Cable, USB for Touch Cable, I/O Protective Cap x 3
Power	
Power Rating	9-36V DC (M12 type)
Control	
Button	5 Keys: - , + , Power , Esc , Enter