



W22L100-67A3POD 21.5" PCAP Touch Chassis Display

Manufacturer part number: W22L100-67A3POD | Outdoor Display



Explore Winmate W22L100-67A3POD, a chassis display featuring 21.5-inch display with 1920x1080 resolution, IP67 for industrial visualization and control rooms.

Display	
Touch / Glass	Projected Capacitive Multi Touch Screen Bonding With Panel (Default), Ture Flat Protection Glass Bonding With Panel (Optional)
Size	21.5 inches
Resolution	1920x1080
Panel Brightness	1500.0 nits
Contrast Ratio	1000:1
View Angles	89,89,89,89
Display Color	16.7M Colors
Active Area	476.64x268.11 mm
Mechanical	
Dimension	529.6 x 342.8 x 58 mm
Weight	8.67 kg
Mounting	VESA mount
Enclosure	Aluminum Housing, Pre finish: Surtec 650, Type II, Class 3 Coating:, Polyester powder coating
Cooling System	Fanless Design
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	-10 deg C to 55 deg C, -25 deg C to 60 deg C (with intelligent heater)
Storage Temperature	-30 deg C to 70 deg C
Shock	MIL-STD-810G Method 516.6 Procedure I
Vibration	MIL-STD-810G Method 514.6 Procedure I
IP rating	IP67
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1 x M12 waterproof connector for 9~36V DC
Serial Port	1x M12 type connector for Touchscreen via USB signal

Video	1x M12 type connector for VGA input, 1x Waterproof connector for HDMI input
SD Card Slot	1 x M12 type connector for Touchscreen via RS232 signal (Optional), 1 x M12 type connector for RS232 Remote Control (Optional)
Indicator	1 x LED Indicator for power, 1 x LED Indicator for lock/unlock status
Control	
Button	1 x "Power" key to power on the device., 1 x "+" key to increase screen brightness., 1 x "-" key to decrease screen brightness., 1 x "Menu" key can Automatically or manually adjusts brightness of the display screen, 1 x Day / Night Mode button, 1 x LED indicator brightness adjustment button, 1 x Ambient Light sensor
Accessory	
Accessory	1 x External open wire Power cable with waterproof connector, 1 x External USB cable with waterproof connector for Touch, 1 x External VGA cable with waterproof connector, 1 x External HDMI cable with waterproof connector, 3 x Waterproof caps, VESA screws
Optional Accessory	100~240V AC to DC Adapter with power cord (Optional), External COM cable with waterproof connector (Optional)