



W22L100-67B2-P(HB) 21.5" G-WIN IP67 Series P-CAP Display

Manufacturer part number: W22L100-67B2-P(HB) | G-WIN Series / IP67



Explore Winmate W22L100-67B2-P(HB), an industrial display featuring 21.5-inch display with 1920x1080 resolution, IP67 for industrial visualization and control...

Display	
Size	21.5 inches
Touch / Glass	Projected Capacitive Multi Touch Screen Bonding With Panel (Default), Ture Flat Protection Glass Bonding With Panel (Optional)
Resolution	1920x1080
Panel Brightness	1000.0 nits
Contrast Ratio	1000:1
View Angles	89,89,89,89
Display Color	16.7M Colors
Active Area	476.64x268.11 mm
Mechanical	
Dimension	529.6 x 342.8 x 58 mm
Weight	8.67 kg
Mounting	VESA mount
Enclosure	Aluminum Housing, Pre finish: Surtec 650, Type II, Class 3 Coating:, Polyester powder coating
Cooling System	Fanless Design
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	-10 deg C to 55 deg C, -40 deg C to 55 deg C (with intelligent heater)
Storage Temperature	-30 deg C to 70 deg C
Shock	MIL-STD-810G Method 516.6 Procedure I
Vibration	MIL-STD-810G Method 514.6 Procedure I
IP rating	IP67
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1x M12 type connector for Touchscreen via USB signal
Serial Port	1 x M12 type connector for RS232 Remote Control (Optional)

Video	1x M12 type connector for VGA input, 1x Waterproof connector for HDMI input
Indicator	1 x LED Indicator for power, 1 x LED Indicator for lock/unlock status
Power Input	1 x M12 waterproof connector for 9~36V DC
Control	
Button	1 x "Power" key to power on the device., 1 x "+" key to increase screen brightness., 1 x "-" key to decrease screen brightness., 1 x "Menu" key can Automatically or manually adjusts brightness of the display screen, 1 x Day / Night Mode button, 1 x LED indicator brightness adjustment button, 1 x Ambient Light sensor
Accessory	
Accessory	External open wire Power cable with waterproof connector, External USB cable with waterproof connector for Touch, External VGA cable with waterproof connector, External HDMI cable with waterproof connector, Waterproof caps, VESA screws
Optional Accessory	100~240V AC to DC 50W Adapter with power cord (Optional), External COM cable with waterproof connector (Optional)
Ordering Information	
Option	W22L100-67B2-G(HB) for Anti Reflective Protection Glass (Optional)