



W22L100-SPA369-P1 21.5" IP69K Stainless P-Series Display

Manufacturer part number: W22L100-SPA369-P1 | Stainless Series



Explore Winmate W22L100-SPA369-P1, an industrial display featuring 21.5-inch display, IP69K for industrial visualization and control rooms.

Display	
Size	21.5 inches
Touch / Glass	Projected Capacitive Multi Touch Screen
Resolution	1920x1080
Panel Brightness	250 nits
Contrast Ratio	3000:1
View Angles	89,89,89,89
Display Color	16.7M Colors
Active Area	476.64x268.11 mm
Mechanical	
Dimension	541 x 337 x 56.2 mm
Mounting	VESA Mount , Yoke Mount
Enclosure	Stainless Housing
Cooling System	Fanless design
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	0 deg C to 45 deg C
Storage Temperature	-20 deg C to 60 deg C
IP rating	IP69K
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1x USB type-A for touch screen control
Video	1x VGA (Default), 1x HDMI (Optional)
Indicator	1 x LED Indicator for power, 1 x LED Indicator for status
Control	
Button	1 x Power Button, 1 x Adjust up button, 1 x Adjust down button, 1 x ESC (Auto) button, 1 x OK (Menu) button

Accessory	
Accessory	1 x Waterproof Conduit 1.5m, 1 x Waterproof Conduit 0.3m, 2 x Elbow for connect the conduit, 1 x AC to DC power adapter with power cord, 1 x External USB cable for touchscreen control, 1 x External HDMI cable, 1 x D-sub15(male) to RJ45 adapter, 1 x D-sub15(female) to RJ45 adapter, 1 x External RJ45 male to male cable, Manual, VESA screws
Optional Accessory	1 x Open wire cable for phoenix connector (Optional), Yoke mount stand kit (Optional)
Power	
Power Rating	12V DC