



W32L300-65A3 32" IP65 Stainless Chassis Display

Manufacturer part number: W32L300-65A3 | Stainless Series



Explore Winmate W32L300-65A3, a chassis display featuring 32-inch display with 1920x1080 resolution, IP65 for industrial visualization and control rooms.

Display	
Size	32.0 inches
Touch / Glass	Protection Glass
Resolution	1920x1080
Panel Brightness	400.0 nits
Contrast Ratio	4000:1
View Angles	89,89,89,89
Display Color	16.7M Colors
Active Area	698.4x392.85 mm
Mechanical	
Dimension	785 x 475 x 87.8 mm
Weight	18Kg
Mounting	VESA Mount
Enclosure	Stainless Housing
Cooling System	Fanless design
Environment	
Operating Humidity	10% to 90% RH, Non-Condensing
Operating Temperature	0 deg C to 45 deg C
Storage Temperature	-20 deg C to 60 deg C
IP rating	IP65
Certification	
Certification	CE, FCC
IO Ports	
Video	1x M12 type connector for VGA input (Default), 1x waterproof DVI input (Optional), 1x waterproof connector for HDMI input (Optional)
Indicator	1 x LED Indicator for power, 1 x LED Indicator for status
Power Input	1 x M12 waterproof connector for 24V DC
Control	

Button	1 x Power Button, 1 x Adjust up button, 1 x Adjust down button, 1 x ESC (Auto) button, 1 x OK (Menu) button
Accessory	
Accessory	100~240V AC to DC Adapter with waterproof connector, Power Cord, External VGA cable with waterproof connector, Waterproof caps, Manual, VESA screws
Optional Accessory	External HDMI cable with waterproof connector (Optional), External DVI cable with waterproof connector (Optional), External Power cable with waterproof connector(For AC power buid in) (Optional)
Power	
Power Rating	24V DC (M12 type)